

# PRODUCT GUIDE



DESIGNED IN USA  
DRIVEN WORLDWIDE



**AMERICAN**  
**ROAD**  **STAR**  
**TIRES**



American Road Star Tires is a innovative brand made with the highest technology to bring you the best quality at the most affordable price. These tires offer superior performance, precision, handling, braking grip, comfort and durability, along with low noise level. American Road Star tire is dedicated to delivering improved savings and operational efficiencies, while reducing environmental impact. These tires are built with your needs and safety in mind and ready to adapt when those needs change.



## CONTENTS

### Passenger Tires

|     |                              |         |
|-----|------------------------------|---------|
|     | American Road Star Sport A/S | page 4  |
|     | American Road Star Pro A/S   | page 10 |
| NEW | American Road Star Run Flat  | page 12 |
|     | American Road Star HP A/S    | page 18 |
| NEW | American Road Star RAZZO A/S | page 20 |

### Light Truck Tires

|     |                          |         |
|-----|--------------------------|---------|
|     | American Road Star H/T   | page 14 |
|     | American Road Star VAN   | page 22 |
|     | American Road Star A/T   | page 24 |
|     | American Road Star M/T   | page 26 |
|     | American Road Star R/T   | page 28 |
| NEW | American Road Star X R/T | page 32 |

|     |                        |            |
|-----|------------------------|------------|
| NEW | American Road Star S/T | page 34-35 |
|     | SEMI-STEEL - ALL-STEEL |            |

### Commercial (TBR) Tires

|                                                                                       |                                              |         |
|---------------------------------------------------------------------------------------|----------------------------------------------|---------|
|  | • STEER/ALL-POSITION - SMART WAY             |         |
|                                                                                       | ARS 1000 - ARS 1100                          | page 38 |
|  | • REGIONAL CLOSED-SHOULDER DRIVE - SMART WAY |         |
|                                                                                       | ARS 2000 - ARS 2200                          | page 40 |
|                                                                                       | • REGIONAL OPEN-SHOULDER DRIVE               |         |
|                                                                                       | ARS 3000                                     | page 42 |
|                                                                                       | • TRAILER                                    |         |
|                                                                                       | ARS 4000                                     | page 44 |
|                                                                                       | • ON-OFF ROAD / MIXED-SERVICE                |         |
|                                                                                       | ARS 5000                                     | page 46 |
|                                                                                       | • REGIONAL PICK-UP/DELIVERY                  |         |
|                                                                                       | ARS 6000                                     | page 48 |



### LIMITED TIRE WARRANTY PLAN

|                            |         |
|----------------------------|---------|
| American Road Star         | page 50 |
| Tire Limited Warranty Plan |         |



UHP All Season  
Ultra High Performance



- Sizes - 14, 15, 16, 17, 18, 19, 20 & 22" Rim Diameter 25, 30, 35, 40, 45, 50, 55 & 60 Series Aspect Ratio
- 500 U.T.Q.G.
- 10/32 Tread Depth
- Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.



SIZES  
COMING  
SOON

| Wheel Dia. | TIRE SIZE |
|------------|-----------|
| 23"        | 285/40R23 |
|            | 325/35R23 |

SPORT A/S

| Wheel Dia. | TIRE SIZE      | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|----------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 14"        | 185/60R14      | 82H                  | 5.0-5.5-6.5           | 5.0-5.5-6.5           | 5 1/2J            | 7.8            | 189              | 578                 | 475 1047           | 300 44                  | 500 A A | /          |
| 15"        | 185/55R15      | 82V                  | 5.0-6.0-6.5           | 5.0-6.0-6.5           | 6J                | 7.8            | 194              | 585                 | 475 1047           | 300 44                  | 500 A A | /          |
|            | 195/50R15      | 82V                  | 5.5-6.0-7.0           | 5.5-6.0-7.0           | 6J                | 8              | 201              | 577                 | 475 1047           | 300 44                  | 500 A A | /          |
|            | 195/55R15      | 85V                  | 5.5-6.0-7.0           | 5.5-6.0-7.0           | 6J                | 8              | 201              | 595                 | 515 1135           | 300 44                  | 500 A A | /          |
| 16"        | NEW 185/55R16  | 87V                  | 5.0-6.0-6.5           | 5.0-6.0-6.5           | 6J                | 7.8            | 194              | 610                 | 545 1201           | 340 49                  | 500 A A | /          |
|            | 195/50ZR16     | 84W                  | 5.5-6-6.5             | 5.5-6-6.5             | 6                 | 7.4            | 201              | 602                 | 560 1102           | 300 44                  | 500A A  | 4PR        |
|            | 195/55ZR16     | 91W                  | 5.5-6.0-7.0           | 5.5-6.0-7.0           | 6J                | 8              | 201              | 620                 | 615 1356           | 340 49                  | 500 A A | /          |
|            | 205/45ZR16     | 87W                  | 6.5-7.0-7.5           | 6.5-7.0-7.5           | 7J                | 8              | 206              | 590                 | 545 1201           | 340 49                  | 500 A A | /          |
|            | 205/50ZR16     | 87W                  | 5.5-6.5-7.5           | 5.5-6.5-7.5           | 6 1/2 J           | 8              | 214              | 612                 | 545 1201           | 300 44                  | 500 A A | /          |
|            | 205/55ZR16     | 94W                  | 5.5-6.5-7.5           | 5.5-6.5-7.5           | 6 1/2J            | 8              | 214              | 632                 | 670 1477           | 340 49                  | 500 A A | /          |
|            | 205/55ZR16     | 94W                  | 6-6.5-7               | 6-6.5-7               | 6.5               | /              | 214              | 632                 | 670 1477           | 340 49                  | 500 A A | 4PR        |
|            | 215/55ZR16     | 97W                  | 6.0-7.0-7.5           | 6.0-7.0-7.5           | 7 J               | 8              | 226              | 642                 | 730 1609           | 340 49                  | 500 A A | /          |
| 17"        | 225/55ZR16     | 95W                  | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8              | 233              | 654                 | 690 1521           | 300 44                  | 500 A A | /          |
|            | 205/40ZR17     | 84W                  | 7.0-7.5-8.0           | /                     | 7 1/2J            | 8              | 212              | 596                 | 500 1102           | 340 49                  | 500 A A | /          |
|            | 205/45ZR17     | 88W                  | 6.5-7.0-7.5           | /                     | 7J                | 8              | 206              | 616                 | 560 1235           | 340 49                  | 500 A A | /          |
|            | 205/50ZR17     | 93W                  | 5.5-6.5-7.5           | 5.5-6.5-7.5           | 6 1/2J            | 8              | 214              | 638                 | 650 1433           | 340 49                  | 500 A A | /          |
|            | 205/55R17      | 95V                  | 5.0-6.5-7.5           | /                     | 6 1/2J            | 8              | 214              | 658                 | 690 1521           | 340 49                  | 500 A A | /          |
|            | 215/45ZR17     | 91W                  | 7.0-8.0               | 7.0-8.0               | 7J                | 8              | 213              | 626                 | 615 1356           | 340 49                  | 500 A A | /          |
|            | 215/45ZR17     | 91W                  | 6.5-7-7.5             | 6.5-7-7.5             | 7                 | /              | 213              | 626                 | 615 1356           | 340 49                  | 420 A A | 4PR        |
|            | 215/50ZR17     | 95W                  | 6.0-7.0-7.5           | 6.0-7.0-7.5           | 7J                | 8              | 226              | 648                 | 690 1521           | 340 49                  | 500 A A | /          |
|            | 215/55ZR17     | 98W                  | 6.0-7.0-7.5           | 6.0-7.0-7.5           | 7J                | 8              | 226              | 668                 | 750 1653           | 340 49                  | 500 A A | /          |
|            | 215/55ZR17     | 98W                  | 6.5-7-7.5             | 6.5-7-7.5             | 7                 | /              | 226              | 668                 | 750 1653           | 340 49                  | 420 A A | 4PR        |
|            | 225/45ZR17     | 94Y                  | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2J            | 8              | 225              | 634                 | 670 1477           | 340 49                  | 500 A A | /          |
|            | 225/45ZR17     | 94Y                  | 7-7.5-8               | 7-7.5-8               | 7.5               | /              | 225              | 634                 | 670 1477           | 340 49                  | 500 A A | 4PR        |
|            | 225/50ZR17     | 98W                  | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8              | 233              | 658                 | 750 1653           | 340 49                  | 500 A A | /          |
|            | 225/55ZR17     | 101W                 | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8              | 233              | 680                 | 825 1819           | 340 49                  | 500 A A | /          |
|            | 235/45ZR17     | 97W                  | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 236              | 644                 | 730 1609           | 340 49                  | 500 A A | /          |
|            | 235/50ZR17     | 100W                 | 7.0-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8              | 245              | 668                 | 800 1764           | 340 49                  | 500 A A | /          |
|            | 235/55ZR17     | 103W                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8.3            | 245              | 690                 | 875 1929           | 340 49                  | 500 A A | /          |
|            | 235/60R17      | 102H                 | 6.5-7.0-8.5           | 6.5-7.0-8.5           | 7J                | 8              | 240              | 714                 | 850 1874           | 300 44                  | 500 A A | /          |
|            | 245/40ZR17     | 95W                  | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 248              | 628                 | 690 1521           | 340 49                  | 500 A A | /          |
| 18"        | NEW 245/45ZR17 | 99W                  | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 243              | 652                 | 775 1709           | 340 49                  | 500 A A | /          |
|            | NEW 215/35ZR18 | 84W                  | 7-7.5-8               | 7-7.5-8               | 7.5               | 7.4            | 218              | 607                 | 500 1102           | 340 49                  | 500 A A | 4PR        |
|            | 215/40ZR18     | 89W                  | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2 J           | 8              | 218              | 629                 | 580 1279           | 340 49                  | 500 A A | /          |
|            | 215/45ZR18     | 89W                  | 7.0-8.0               | 7.0-8.0               | 7J                | 8              | 213              | 651                 | 580 1279           | 300 44                  | 500 A A | /          |
|            | NEW 215/50R18  | 92V                  |                       |                       | 7.5               | 10             | 217              | 673                 | 630 1389           | 300 44                  | 600AA   | 4PR        |
|            | 215/55R18      | 95V                  | 6.0-7.0-7.5           | 6.0-7.0-7.5           | 7J                | 8              | 226              | 693                 | 690 1521           | 300 44                  | 500 A A | /          |
|            | 225/40ZR18     | 92W                  | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 230              | 637                 | 630 1389           | 340 49                  | 500 A A | /          |
|            | 225/45ZR18     | 95W                  | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2J            | 8              | 225              | 659                 | 690 1521           | 340 49                  | 500 A A | /          |
| 18"        | 225/50ZR18     | 99W                  | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8              | 233              | 683                 | 775 1709           | 340 49                  | 500 A A | /          |
|            | 225/55R18      | 102V                 | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8              | 233              | 705                 | 1030 2271          | 340 49                  | 500 A A | /          |



UHP All Season  
Ultra High Performance

AMERICAN  
ROADSTAR SPORT A/S



PATTERN INTRODUCTIONS

OUTSIDE

INSIDE

1. 4 wide longitudinal grooves provide good water evacuation for excellent handling performance on wet roads.

2. Outside Anti Eccentric wear block design  
Anti eccentric wear blocks on outer shoulder can increase the tread contact area at braking to obtain uniform contact pressure, which can avoid eccentric wear.

3. Partial Slanted Grooves  
interrupt air flow across the tread to decrease noise.  
Partial slanted grooves also can provide stability during cornering

4. Wide Grooves and fine sipes cut through water film to provide wet traction, and greatly reduce noise , providing a comfortable driving experience.

5. Silent pitch variation and sequence design Optimization of pitch width and sequence effectively reduce the noise resonance, resulting in a quieter ride.

SPORT A/S

| Wheel Dia. | TIRE SIZE      | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|----------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 18"        | 235/40ZR18     | 95W                  | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 241              | 645                 | 690 1521           | 340 49                  | 500 A A | /          |
|            | 235/45ZR18     | 98W                  | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 236              | 669                 | 750 1653           | 340 49                  | 500 A A | /          |
|            | 235/45ZR18     | 98W                  | 7.5-8-8.5             | 7.5-8-8.5             | 8                 |                | 236              | 669                 | 750 1653           | 340 49                  | 500 A A | 4PR        |
|            | 235/50ZR18     | 101W                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8              | 245              | 693                 | 825 1819           | 340 49                  | 500 A A | /          |
|            | 245/40ZR18     | 97W                  | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 248              | 653                 | 730 1609           | 340 49                  | 500 A A | /          |
|            | 245/45ZR18     | 100W/Y               | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 243              | 677                 | 800 1764           | 340 49                  | 500 A A | /          |
|            | 245/50ZR18     | 100W                 | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2J            | 8              | 253              | 703                 | 800 1764           | 300 44                  | 500 A A | /          |
|            | 245/55ZR18     | 103W                 | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2J            | 8              | 253              | 727                 | 875 1929           | 300 44                  | 500 A A | /          |
|            | 255/35ZR18     | 94W                  | 8.5-9.0-10.0          | 8.5-9.0-10.0          | 9 J               | 8              | 260              | 635                 | 670 1477           | 340 49                  | 500 A A | /          |
|            | 255/40ZR18     | 99W                  | 8.5-9.0-10.0          | 8.5-9.0-10.0          | 9J                | 8              | 260              | 661                 | 775 1709           | 340 49                  | 500 A A | /          |
|            | 255/55ZR18     | 109W                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J                | 8              | 265              | 737                 | 1030 2271          | 340 49                  | 500 A A | /          |
|            | NEW 255/60R18  | 112V                 | 7-7.5-8               | 7-7.5-8               | 7.5               | 7.6            | 260              | 763                 | 1120 2469          | 340 49                  | 500 A A | 4PR        |
|            | 265/35ZR18     | 97W                  | 9.0-9.5-10.5          | 9.0-9.5-10.5          | 9 1/2 J           | 8              | 271              | 643                 | 730 1609           | 340 49                  | 500 A A | /          |
|            | NEW 275/40ZR18 | 99Y                  | 9-9.5-10              | 9-9.5-10              | 9.5               | 7.6            | 278              | 677                 | 775 1709           | 300 44                  | 500 A A | 4PR        |
| 19"        | 225/40ZR19     | 93W                  | 7.5-8.0-9.0           | /                     | 8J                | 8              | 230              | 663                 | 650 1433           | 340 49                  | 500 A A | /          |
|            | 225/45ZR19     | 96W                  | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2 J           | 8              | 225              | 685                 | 710 1565           | 340 49                  | 500 A A | /          |
|            | 225/55R19      | 103XL/V              | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8              | 233              | 731                 | 875 1929           | 340 50                  | 500 A A | /          |
|            | 235/35ZR19     | 91W                  | 8.0-8.5-9.5           | /                     | 8 1/2J            | 8              | 241              | 647                 | 615 1356           | 340 49                  | 500 A A | /          |
|            | 235/40ZR19     | 96W                  | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 241              | 671                 | 710 1565           | 340 49                  | 500 A A | /          |
|            | 235/40ZR19     | 96W                  | 8-8.5-9               | 8-8.5-9               | 8.5               |                | 241              | 671                 | 710 1565           | 340 49                  | 500AA   | 4PR        |
|            | 235/45ZR19     | 99W                  | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 236              | 695                 | 775 1709           | 340 49                  | 500 A A | /          |
|            | 235/50ZR19     | 103W                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8              | 245              | 719                 | 875 1929           | 340 49                  | 500 A A | /          |
|            | 235/55R19      | 105V                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8              | 245              | 741                 | 925 2039           | 340 49                  | 500 A A | /          |
|            | 235/55R19      | 105V                 | 7-7.5-8               | 7-7.5-8               | 7.5               |                | 245              | 741                 | 925 2039           | 340 49                  | 500 A A | 4PR        |
|            | NEW 235/65R19  | 109V                 | 6.5-7-7.5             | 6.5-7-7.5             | 7                 | 7.6            | 240              | 789                 | 1030 2271          | 340 49                  | 500 A A | 4PR        |
|            | 245/35ZR19     | 97W                  | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 248              | 655                 | 730 1609           | 340 49                  | 500 A A | /          |
|            | 245/40ZR19     | 98W/Y                | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 248              | 679                 | 750 1653           | 340 49                  | 500 A A | /          |
|            | 245/45ZR19     | 102W                 | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8 J               | 8              | 243              | 703                 | 850 1874           | 340 49                  | 500 A A | /          |
|            | 245/50ZR19     | 105XL/W              | /                     | 7.0-7.5-8.5           | 7 1/2J            | 8              | 253              | 729                 | 925 2039           | 340 50                  | 500 A A | /          |
|            | 245/55ZR19     | 103W                 | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2J            | 8              | 253              | 753                 | 875 1929           | 300 44                  | 500 A A | /          |
|            | 255/35ZR19     | 96W                  | 8.5-9.0-10.0          | /                     | 9J                | 8              | 260              | 661                 | 710 1565           | 340 49                  | 500 A A | /          |
|            | 255/40ZR19     | 100W                 | 8.5-9.0-10.0          | 8.5-9.0-10.0          | 9J                | 8              | 260              | 687                 | 800 1764           | 340 49                  | 500 A A | /          |
|            | 255/45ZR19     | 104W                 | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 255              | 713                 | 900 1984           | 340 49                  | 500 A A | /          |
|            | 255/55ZR19     | 111W                 | 7.0-8.0-9.0           | /                     | 8J                | 8              | 265              | 763                 | 1090 2403          | 340 49                  | 500 A A | /          |
|            | 265/30ZR19     | 93W                  | 9.0-9.5-10.0          | /                     | 9 1/2J            | 8              | 271              | 643                 | 650 1433           | 340 49                  | 500 A A | /          |
|            | 265/35ZR19     | 98XL/Y               | 9.0-9.5-10.5          | /                     | 9 1/2J            | 8              | 271              | 669                 | 750 1653           | 340 50                  | 500 A A | /          |
|            | 265/50ZR19     | 110XL/W              | 7.5-8.5-9.5           | /                     | 8 1/2J            | 8              | 277              | 749                 | 1060 2337          | 340 49                  | 500 A A | /          |
|            | 275/30ZR19     | 96W                  | 9.0-9.5-10.0          | 9.0-9.5-10.0          | 9 1/2J            | 8              | 278              | 649                 | 710 1565           | 340 49                  | 500 A A | /          |
|            | 275/35ZR19     | 100W                 | 9.0-9.5-11.0          | /                     | 9 1/2J            | 8              | 278              | 675                 | 800 1764           | 340 49                  | 500 A A | /          |
|            | 275/40ZR19     | 101Y                 | 9.0-9.5-11.0          | 9.0-9.5-11.0          | 9 1/2J            | 8              | 278              | 703                 | 825 1819           | 300 44                  | 500 A A | /          |



SPORT A/S

| Wheel Dia. | TIRE SIZE      | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|----------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 19"        | NEW 275/45ZR19 | 108W                 | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.6            | 273              | 731                 | 1000 2205          | 340 49                  | 500 A A | 4PR        |
|            | 275/55R19      | 111V                 | 7.5-8.5-9.5           | /                     | 8 1/2J            | 8.3            | 284              | 785                 | 1090 2403          | 300 44                  | 500 A A | /          |
| 20"        | 225/35ZR20     | 93W                  | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 230              | 666                 | 650 1433           | 340 49                  | 500 A A | /          |
|            | 235/35ZR20     | 92XL/Y               | 8.0-8.5-9.5           | /                     | 8 1/2J            | 8              | 241              | 672                 | 630 1389           | 340 50                  | 500 A A | /          |
|            | 235/45ZR20     | 100XL/W              | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 236              | 720                 | 800 1764           | 340 50                  | 500 A A | /          |
|            | 235/50ZR20     | 104XL/W              | 6.5-7.5-8.5           | /                     | 7 1/2J            | 8              | 245              | 744                 | 900 1984           | 340 50                  | 500 A A | /          |
|            | 235/55ZR20     | 102W                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8              | 245              | 766                 | 850 1874           | 300 44                  | 500 A A | /          |
|            | 235/55ZR20     | 102W                 | 7-7.5-8               | 7-7.5-8               | 7.5               |                | 245              | 766                 | 850 1874           | 300 44                  | 500 A A | 4PR        |
|            | 245/35ZR20     | 95W                  | 8.0-8.5-9.5           | /                     | 8 1/2J            | 8              | 248              | 680                 | 690 1521           | 340 49                  | 500 A A | /          |
|            | 245/40ZR20     | 99W/Y                | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 248              | 704                 | 775 1709           | 340 49                  | 500 A A | /          |
|            | 245/45ZR20     | 103W                 | 7.5-8.0-9.0           | 7.5-8.0-9.0           | 8J                | 8              | 243              | 728                 | 875 1929           | 340 49                  | 500 A A | /          |
|            | 245/45ZR20     | 103W                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 |                | 243              | 728                 | 875 1929           | 340 49                  | 500 A A | 4PR        |
|            | 255/35ZR20     | 97W                  | 8.5-9.0-10.0          | 8.5-9.0-10.0          | 9 J               | 8              | 260              | 686                 | 730 1609           | 340 49                  | 500 A A | /          |
|            | NEW 255/40ZR20 | 101W                 | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.6            | 260              | 712                 | 825 1819           | 340 49                  | 500 A A | 4PR        |
|            | 255/45R20      | 105W                 | 8.0-8.5-9.5           | 8.0-8.5-9.5           | 8 1/2J            | 8              | 255              | 738                 | 925 2039           | 340 49                  | 500 A A | /          |
|            | 255/50ZR20     | 109V                 | 7.0-8.0-8.5           | 7.0-8.0-9.0           | 8 J               | 8              | 265              | 764                 | 1030 2271          | 340 49                  | 500 A A | /          |
|            | 255/55R20      | 110H                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J                | 8              | 265              | 788                 | 1060 2337          | 340 49                  | 500 A A | /          |
|            | NEW 255/60R20  | 113Y                 | /                     | /                     | 9                 | 6.6            | 257              | 741                 | 1150 2535          | 340 50                  | 540AA   | 4PR        |
|            | NEW 265/35ZR20 | 99Y                  | 9-9.5-10              | 9-9.5-10              | 9.5               | 7.6            | 271              | 694                 | 775 1709           | 340 49                  | 500 A A | 4PR        |
|            | 265/45ZR20     | 108W                 | 8.5-9.0-10.0          | /                     | 9 J               | 8              | 266              | 746                 | 1000 2205          | 340 49                  | 500 A A | /          |
|            | 265/50R20      | 111V                 | 7.5-8.5-9.5           | 7.5-8.5-9.5           | 8 1/2J            | 8              | 277              | 774                 | 1090 2403          | 340 49                  | 500 A A | /          |
|            | 275/30ZR20     | 97W                  | 9.0-9.5-10.0          | 9.0-9.5-10.0          | 9 1/2J            | 8              | 278              | 674                 | 730 1609           | 340 49                  | 500 A A | /          |
|            | 275/35ZR20     | 102W                 | 9.0-9.5-11.0          | 9.0-9.5-11.0          | 9 1/2J            | 8              | 278              | 700                 | 850 1874           | 340 49                  | 500 A A | /          |
|            | 275/40ZR20     | 106W                 | 9.0-9.5-11.0          | 9.0-9.5-11.0          | 9 1/2 J           | 8.3            | 278              | 728                 | 950 2094           | 340 49                  | 500 A A | /          |
|            | 275/50ZR20     | 113XL/Y              | 7.5-8.5-9.5           | /                     | 8 1/2J            | 8.3            | 284              | 784                 | 1150 2535          | 340 50                  | 500 A A | /          |
|            | 285/30ZR20     | 99XL/Y               | 9.5-10.0-10.5         | 9.5-10.0-10.5         | 10J               | 8              | 290              | 680                 | 775 1709           | 340 50                  | 500 A A | /          |
|            | NEW 285/35ZR20 | 104XL/W              | 9.5-10.0-11.0         | 9.5-10.0-11.0         | 10J               | 8.3            | 290              | 708                 | 900 1984           | 340 49                  | 500 A A | /          |
|            | 295/40ZR20     | 110XL/W              | 10.0-10.5-11.5        | 10.0-10.5-11.5        | 10 1/2J           | 8.3            | 301              | 744                 | 1060 2337          | 340 49                  | 500 A A | /          |
|            | NEW 295/45ZR20 | 114Y                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 296              | 774                 | 1180 2601          | 340 49                  | 500AA   | 4PR        |
|            | 305/30ZR20     | 103XL/W              | /                     | 7.0-8.5-9.0           | 11 J              | 8.3            | 313              | 692                 | 875 1929           | 340 49                  | 500 A A | /          |
|            | NEW 305/35ZR20 | 107Y                 | 10.5-11-11.5          | 10.5-11-11.5          | 11                | 7.8            | 313              | 722                 | 975 2149           | 340 49                  | 500 A A | 4PR        |
|            | 315/35ZR20     | 110W                 | 10.5-11.0-12.5        | 10.5-11.0-12.5        | 11 J              | 8.3            | 320              | 728                 | 1060 2337          | 340 49                  | 500 A A | /          |
| 21"        | NEW 245/35ZR21 | 96XL/Y               | 8.0-8.5-9.5           | /                     | 8 1/2J            | 8              | 248              | 705                 | 710 1565           | 340 50                  | 500 A A | /          |
|            | NEW 245/40ZR21 | 100Y                 | /                     | /                     | 9.5               | 10             | 245              | 728                 | 799 1763           | 330 49                  | 320AA   | 4PR        |
|            | 255/35ZR21     | 98Y                  | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.8            | 260              | 711                 | 750 1653           | 340 49                  | 500 A A | 4PR        |
|            | 255/40ZR21     | 105Y                 | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.8            | 260              | 737                 | 925 2039           | 340 49                  | 500 A A | 4PR        |
|            | 265/35ZR21     | 101XL/Y              | 9.0-9.5-10.5          | /                     | 9 1/2J            | 8              | 271              | 719                 | 825 1819           | 340 50                  | 500 A A | /          |
|            | 265/40ZR21     | 105XL/Y              | 9.0-9.5-10.5          | /                     | 9 1/2J            | 8              | 271              | 745                 | 925 2039           | 340 50                  | 500 A A | /          |
|            | NEW 265/45ZR21 | 108Y                 | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.8            | 266              | 771                 | 1000 2205          | 340 49                  | 500 A A | 4PR        |
|            | 275/35ZR21     | 103XL/Y              | 9.0-9.5-11.0          | /                     | 9 1/2J            | 8              | 278              | 725                 | 875 1929           | 340 50                  | 500 A A | /          |
|            | 275/40ZR21     | 109XL/Y              | 9.0-9.5-11.0          | /                     | 9 1/2J            | 8.3            | 278              | 753                 | 1030 2271          | 340 50                  | 500 A A | /          |
|            | 275/45ZR21     | 110XL/Y              | 8.5-9.0-10.5          | /                     | 9J                | 8.3            | 273              | 781                 | 1060 2337          | 340 50                  | 500 A A | /          |

SPORT A/S

| Wheel Dia. | TIRE SIZE      | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|----------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 21"        | 275/50ZR21     | 113Y                 | 8-8.5-9               | 8-8.5-9               | 8.5               | 7.8            | 284              | 809                 | 1150 2335          | 340 49                  | 500 A A | 4PR        |
|            | 285/30ZR21     | 100Y                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 290              | 705                 | 800 1764           | 340 49                  | 500AA   | 4PR        |
|            | 285/35ZR21     | 108XL/Y              | 9.5-10.0-11.0         | /                     | 10J               | 8.3            | 290              | 733                 | 1000 2205          | 340 50                  | 500 A A | /          |
|            | 285/40ZR21     | 109XL/Y              | 9.5-10.0-11.0         | /                     | 10J               | 8.3            | 290              | 761                 | 1030 2271          | 340 50                  | 500 A A | /          |
|            | 285/45ZR21     | 113XL/W              | 9.0-9.5-10.5          | /                     | 9 1/2J            | 8.3            | 285              | 789                 | 1150 2535          | 340 50                  | 500 A A | /          |
|            | 295/35ZR21     | 107XL/Y              | 10.0-10.5-11.5        | /                     | 10 1/2J           | 8.3            | 301              | 739                 | 975 2149           | 340 50                  | 500 A A | /          |
|            | 295/40ZR21     | 111XL/Y              | 10.0-10.5-11.5        | /                     | 10 1/2J           | 8.3            | 301              | 769                 | 1090 2403          | 340 50                  | 500 A A | /          |
|            | 315/30ZR21     | 105XL/Y              | 10.5-11.0-11.5        | /                     | 11J               | 8.3            | 320              | 723                 | 925 2039           | 340 50                  | 500 A A | /          |
|            | 315/35ZR21     | 111XL/Y              | 10.5-11.0-12.5        | /                     | 11J               | 8.3            | 320              | 753                 | 1090 2403          | 340 50                  | 500 A A | /          |
|            | 315/40ZR21     | 111Y                 | 10.5-11.0-12.5        | /                     | 11J               | 8.3            | 320              | 785                 | 1090 2403          | 300 44                  | 500 A A | /          |
|            | 325/30ZR21     | 110XL/Y              | 11.0-11.5-12.0        | /                     | 11 1/2J           | 8.3            | 331              | 729                 | 1060 2337          | 340 50                  | 500 A A | /          |
| 22"        | NEW 225/30ZR22 | 89W                  | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 7.8            | 230              | 695                 | 545 1201           | 340 49                  | 500 A A | 4PR        |
|            | 255/30ZR22     | 95W                  | 8.5-9.0-9.5           | /                     | 9 J               | 8              | 260              | 713                 | 690 1521           | 340 49                  | 500 A A | /          |
|            | NEW 265/30ZR22 | 97W                  | 9-9.5-10              | 9-9.5-10              | 9.5               | 7.8            | 271              | 719                 | 730 1609           | 340 49                  | 500AA   | 4PR        |
|            | 265/35ZR22     | 102XL/W              | 9.0-9.5-10.5          | /                     | 9 1/2J            | 8              | 271              | 745                 | 850 1874           | 340 49                  | 500 A A | /          |
|            | 275/35ZR22     | 107XL/Y              | 9.0-9.5-11.0          | /                     | 9 1/2J            | 8              | 278              | 751                 | 975 2149           | 340 50                  | 500 A A | /          |
|            | 275/40ZR22     | 108XL/Y              | 9.0-9.5-11.0          | /                     | 9 1/2J            | 8.3            | 278              | 779                 | 1000 2205          | 340 50                  | 500 A A | /          |
|            | 275/50R22      | 115XL/H              | 7.5-8.5-9.5           | 7.5-8.5-9.5           | 8 1/2J            | 8.3            | 284              | 835                 | 1215 2679          | 340 50                  | 500 A A | /          |
|            | 285/35ZR22     | 106W                 | 9.5-10.0-11.0         | /                     | 10J               | 8.3            | 290              | 759                 | 950 2094           | 340 49                  | 500 A A | /          |
|            | 285/40ZR22     | 110XL/Y              | 9.5-10.0-11.0         | /                     | 10J               | 8.3            | 290              | 787                 | 1060 2337          | 340 50                  | 500 A A | /          |
|            | NEW 295/25ZR22 | 97Y                  | 10-10.5-11            | 10-10.5-11            | 10.5              | 7.8            | 301              | 707                 | 730 1609           | 340 49                  | 500AA   | 4PR        |
|            | 295/30ZR22     | 110XL/Y              | 10.0-10.5-11.0        | /                     | 10 1/2J           | 8.3            | 301              | 737                 | 1060 2337          | 340 50                  | 500 A A | /          |
|            | NEW 295/40ZR22 | 112W                 | /                     | /                     | 11.5              | 9              | 295              | 795                 | 1119 2469          | 340 50                  | 420AA   | 4PR        |
|            | NEW 305/25ZR22 | 103Y                 | 10.5-11-11.5          | 10.5-11-11.5          | 11                | 7.8            | 313              | 711                 | 775 1709           | 340 49                  | 500AA   | 4PR        |
|            | NEW 305/45R22  | 118V                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 303              | 833                 | 1320 2910          | 340 49                  | 500AA   | 4PR        |
|            | NEW 315/25ZR22 | 101Y                 | 11-11.5-12            | 11-11.5-12            | 11.5              | 7.8            | 325              | 717                 | 825 1819           | 340 49                  | 500AA   | 4PR        |
|            | 315/30ZR22     | 107XL/Y              | 10.5-11.0-11.5        | /                     | 11J               | 8.3            | 320              | 749                 | 975 2149           | 340 50                  | 500 A A | /          |
|            | 315/35ZR22     | 111XL/Y              | 10.5-11.0-12.5        | /                     | 11J               | 8.3            | 320              | 779                 | 1090 2403          | 340 50                  | 500 A A | /          |
|            | NEW 325/40ZR22 | 114W                 | 11-11.5-12            | 11-11.5-12            | 11.5              | 7.8            | 331              | 819                 | 1180 2601          | 300 44                  | 500AA   | 4PR        |
| 24"        | NEW 245/30ZR24 | 94W                  | 8-8.5-9               | 8-8.5-9               | 8.5               | 7.8            | 248              | 758                 | 670 1477           | 340 49                  | 500 A A | 4PR        |
|            | NEW 255/25ZR24 | 95W                  | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.8            | 260              | 738                 | 690 1521           | 340 49                  | 500 A A | 4PR        |
|            | NEW 255/30ZR24 | 97W                  | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 7.8            | 260              | 764                 | 730 1609           | 340 49                  | 500AA   | 4PR        |
|            | NEW 275/25ZR24 | 96W                  | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 283              | 748                 | 710 1565           | 340 49                  | 500AA   | 4PR        |
|            | NEW 285/30ZR24 | 103W                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 290              | 782                 | 875 1929           | 340 49                  | 500AA   | 4PR        |
|            | NEW 285/35ZR24 | 108W                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 290              | 810                 | 1000 2205          | 340 49                  | 500AA   | 4PR        |
|            | NEW 285/40R24  | 112V                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 290              | 838                 | 1120 2469          | 340 49                  | 500AA   | 4PR        |
|            | NEW 295/30ZR24 | 104Y                 | 10-10.5-11            | 10-10.5-11            | 10.5              | 7.8            | 301              | 788                 | 900 1984           | 340 49                  | 500 A A | 4PR        |
|            | NEW 295/35R24  | 110V                 | 10-10.5-11            | 10-10.5-11            | 10.5              | 7.8            | 301              | 816                 | 1060 2337          | 340 49                  | 500AA   | 4PR        |
|            | NEW 305/30ZR24 | 107W                 | 10.5-11-11.5          | 10.5-11-11.5          | 11                | 7.8            | 313              | 794                 | 975 2149           | 340 49                  | 500AA   | 4PR        |
| 26"        | NEW 275/25ZR26 | 98W                  | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 7.8            | 283              | 798                 | 750 1653           | 340 49                  | 500AA   | 4PR        |
|            | NEW 295/25ZR26 | 102W                 | 10-10.5-11            | 10-10.5-11            | 10.5              | 7.8            | 301              | 808                 | 850 1874           | 340 49                  | 500AA   | 4PR        |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.



TOURING All-Season Tires




- Sizes - 14, 15, 16, 17 & 18" Rim
- Diameters 60, 65 & 70 Series
- Aspect Ratio
- 500 U.T.Q.G.
- 10/32 Tread Depth
- Uniquely Wide Flat Tread Radius
- Produces excellent steering progression and ride comfort.
- Jointless Nylon Band
- Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts
- Strengthen the overall tread area.
- Provides stability, excellent wear character & long mileage.



PATTERN INTRODUCTIONS



4 wide longitudinal grooves provide good drainage performance, keep excellent handling performance in wet road.



Grooves with different thickness and sipes design can destroy water film to guarantee the drainage performance effectively , and reduce noise greatly , providing a comfortable driving experience.



The middle portion continuous strong tire tread ribs can improve the steering stability and straight performance at high speeds, to ensure stability and security.



Optimization of pitch width and sequence effectively reduce the noise resonance, resulting in a quieter ride.

PRO A/S

| Wheel Dia. | TIRE SIZE     | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|---------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 13"        | NEW 165/65R13 | 77H                  | /                     | /                     | 5                 | 6.6            | 170              | 544                 | 412 908            | 300 44                  | 400A A  | 4PR        |
|            | NEW 175/60R13 | 77H                  | /                     | /                     | 6                 | 7.3            | 175              | 540                 | 411 908            | 250 36                  | 400A A  | 4PR        |
|            | NEW 175/70R13 | 82T                  | /                     | /                     | 5                 | 6.6            | 177              | 576                 | 475 1047           | 300 44                  | 400A A  | 4PR        |
|            | NEW 185/60R13 | 80H                  | /                     | /                     | 6.5               | 7              | 185              | 551                 | 450 992            | 300 44                  | 400A A  | 4PR        |
| 14"        | NEW 155/65R14 | 79H                  | /                     | /                     | 4.5               | 6.6            | 157              | 558                 | 387 853            | 300 44                  | 400A A  | 4PR        |
|            | NEW 165/60R14 | 79H                  | /                     | /                     | 6                 | 7              | 165              | 554                 | 387 963            | 250 51                  | 400A A  | 4PR        |
|            | NEW 165/65R14 | 79H                  | 4.5-5-5.5             | 4.5-5-5.5             | 5                 | 7.4            | 170              | 570                 | 437 963            | 300 44                  | 500 A A | 4PR        |
|            | NEW 165/70R14 | 81T                  | /                     | /                     | 5                 | 6.6            | 170              | 588                 | 462 1019           | 300 44                  | 400A A  | 4PR        |
|            | 175/65R14     | 82H                  | 5.0-6.0               | 5.0-6.0               | 5J                | 7.8            | 177              | 584                 | 475 1047           | 300 44                  | 500 A A | /          |
|            | 175/70R14     | 88H                  | 4.5-5.0-6.0           | 4.5-5.0-6.0           | 5J                | 7.8            | 177              | 602                 | 560 1235           | 340 49                  | 500 A A | /          |
|            | 185/65R14     | 86H                  | 5.0-5.5-6.5           | 5.0-5.5-6.5           | 5 1/2J            | 7.8            | 189              | 596                 | 530 1168           | 300 44                  | 500 A A | /          |
|            | 185/70R14     | 88H                  | 4.5-5.5-6.0           | 4.5-5.5-6.0           | 5 1/2J            | 7.8            | 189              | 616                 | 560 1235           | 300 44                  | 500 A A | /          |
| 15"        | 195/70R14     | 91H                  | 5.0-6.0-6.5           | 5.0-6.0-6.5           | 6J                | 8              | 201              | 630                 | 615 1356           | 300 44                  | 500 A A | /          |
|            | 205/70R14     | 98H                  | 5.0-6.0-7.0           | 5.0-6.0-7.0           | 6J                | 8              | 209              | 644                 | 750 1653           | 340 49                  | 500 A A | /          |
|            | 175/65R15     | 84H                  | 5.0-6.0               | 5.0-6.0               | 5J                | 7.8            | 177              | 609                 | 500 1102           | 300 44                  | 500 A A | /          |
|            | 185/60R15     | 84H                  | 5.0-5.5-6.5           | 5.0-5.5-6.5           | 5 1/2J            | 7.8            | 189              | 603                 | 500 1102           | 300 44                  | 500 A A | /          |
|            | 185/65R15     | 88H                  | 5.0-5.5-6.5           | 5.0-5.5-6.5           | 5 1/2J            | 7.8            | 189              | 621                 | 560 1235           | 300 44                  | 500 A A | /          |
|            | 195/60R15     | 88H                  | 5.5-6.0-7.0           | 5.5-6.0-7.0           | 6J                | 8              | 201              | 615                 | 560 1235           | 300 44                  | 500 A A | /          |
|            | 195/65R15     | 91H                  | 5.5-6.0-7.0           | 5.5-6.0-7.0           | 6J                | 8              | 201              | 635                 | 615 1356           | 300 44                  | 500 A A | /          |
|            | 195/65R15     | 91H                  | 5.5-6-6.5             | 5.5-6-6.5             | 6                 | /              | 201              | 635                 | 615 1356           | 300 44                  | 500 A A | 4PR        |
|            | 205/60R15     | 91V                  | 5.5-6.0-7.5           | 5.5-6.0-7.5           | 6J                | 8              | 209              | 627                 | 615 1356           | 300 44                  | 500 A A | /          |
|            | 205/65R15     | 94H                  | 5.5-6.0-7.5           | 5.5-6.0-7.5           | 6J                | 8              | 209              | 647                 | 670 1477           | 300 44                  | 500 A A | /          |
|            | 205/70R15     | 96H                  | 5.0-6.0-7.0           | 5.0-6.0-7.0           | 6J                | 8              | 209              | 669                 | 710 1565           | 300 44                  | 500 A A | /          |
|            | 215/65R15     | 100H                 | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8              | 221              | 661                 | 800 1764           | 340 49                  | 500 A A | /          |
| 16"        | 215/70R15     | 98T                  | 5.5-6.5-7.0           | 5.5-6.5-7.0           | 6 1/2J            | 8.3            | 221              | 683                 | 750 1653           | 300 44                  | 500 A A | /          |
|            | 225/70R15     | 100T                 | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8              | 228              | 697                 | 800 1764           | 300 44                  | 500 A A | /          |
|            | 185/60R16     | 86H                  | 5.0-5.5-6.5           | 5.0-5.5-6.5           | 5 1/2J            | 7.8            | 189              | 628                 | 530 1168           | 300 44                  | 500 A A | /          |
|            | 205/60R16     | 96V                  | 5.5-6.0-7.5           | 5.5-6.0-7.5           | 6J                | 8              | 209              | 652                 | 710 1565           | 340 49                  | 500 A A | /          |
|            | 205/65R16     | 95V                  | 5.5-6.0-7.5           | 5.5-6.0-7.5           | 6J                | 7.8            | 209              | 672                 | 690 1521           | 300 44                  | 500 A A | /          |
|            | 205/70R16     | 97H                  | 5.0-6.0-7.0           | 5.0-6.0-7.0           | 6J                | 8              | 209              | 694                 | 730 1609           | 300 44                  | 500 A A | /          |
|            | 215/60R16     | 95V                  | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8.3            | 221              | 664                 | 690 1521           | 300 44                  | 500 A A | /          |
|            | 215/65R16     | 102H                 | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8              | 221              | 686                 | 850 1874           | 340 49                  | 500 A A | /          |
|            | 225/60R16     | 98H                  | 6.0-6.5-8.0           | 6.0-6.5-8.0           | 6 1/2J            | 8.3            | 228              | 676                 | 750 1653           | 300 44                  | 500 A A | /          |
|            | 225/65R16     | 100H                 | 6.0-6.5-8.0           | 6.0-6.5-8.0           | 6 1/2J            | 8              | 228              | 698                 | 800 1764           | 300 44                  | 500 A A | /          |
| 17"        | 235/65R16     | 107H                 | 6.5-7.0-8.5           | 6.5-7.0-8.5           | 7J                | 8              | 240              | 712                 | 975 2149           | 340 49                  | 500 A A | /          |
|            | 215/60R17     | 100H                 | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8              | 221              | 690                 | 800 1764           | 340 49                  | 500 A A | /          |
|            | 215/65R17     | 99H                  | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8              | 221              | 712                 | 775 1709           | 300 44                  | 500 A A | /          |
|            | 225/60R17     | 99V                  | 6.0-6.5-8.0           | 6.0-6.5-8.0           | 6 1/2J            | 8.3            | 228              | 702                 | 775 1709           | 300 44                  | 500 A A | /          |
| 18"        | 225/60R18     | 104V                 | 6.0-6.5-8.0           | 6.0-6.5-8.0           | 6 1/2J            | 8              | 228              | 727                 | 900 1964           | 340 49                  | 500 A A | /          |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.



COMING SOON

RUN FLAT 

NEW

|     |           |     |           |
|-----|-----------|-----|-----------|
| 16" | 195/55R16 | 17" | 205/45R17 |
|     | 205/55R16 |     | 205/50R17 |
|     |           |     | 205/55R17 |
|     |           |     | 225/45R17 |
|     |           |     | 225/50R17 |
|     |           |     | 225/55R17 |

RUN FLAT 



COMING SOON

RUN FLAT 

NEW

|     |           |     |           |     |           |
|-----|-----------|-----|-----------|-----|-----------|
| 18" | 205/40R18 | 19" | 225/40R19 | 20" | 245/35R20 |
|     | 225/40R18 |     | 225/45R19 |     | 245/40R20 |
|     | 225/45R18 |     | 235/45R19 |     | 245/45R20 |
|     | 225/50R18 |     | 235/55R19 |     | 255/45R20 |
|     | 235/50R18 |     | 245/40R19 |     | 275/30R20 |
|     | 235/55R18 |     | 245/45R19 |     | 275/35R20 |
|     | 235/60R18 |     | 245/50R19 |     | 275/40R20 |
|     | 245/40R18 |     | 255/35R19 |     | 275/45R20 |
|     | 245/45R18 |     | 255/50R19 |     | 315/35R20 |
|     | 245/50R18 |     | 265/50R19 | 21" | 275/40R21 |
| 18" | 255/35R18 | 19" | 275/35R19 |     | 275/45R21 |
|     | 255/40R18 |     | 275/40R19 |     | 285/35R21 |
|     |           |     |           |     | 315/35R21 |
|     |           |     |           |     | 275/40R22 |
|     |           |     |           | 22" | 315/35R22 |

RUN FLAT 



RUN FLAT 

**HIGH STABILITY CANTERING RIB**

The solid rib in the center of the tire ensures straight-line driving stability

**WET GRIP GROOVE DESIGN**

Four wide, longitudinal grooves channel road water, while lateral grooves work to direct it out from under the tire

**LOW TREAD WEAR SHOULDER DESIGN**

The shoulder is integrated with heat-resisting bars to keep the tread blocks stable and protect them from irregular wear. For the same reason, the design also improves high-speed cornering stability

**FUEL-SAVING TREAD COMPOUND**

The American Roadstar Run Flat advanced tread compound reduces rolling resistance, which helps boost fuel efficiency and lower exhaust emissions

**QUIET-RIDE PITCH ALIGNMENT**

Optimized tread pitch width and alignment for quiet resonance and reduced road noise



RUN FLAT 

**OPTIMIZED TREAD DESIGN**

Our computer-aided design has optimized the tread pitch and alignment which reduces road noise levels at higher speeds

**WET-GRIP SIPES AND GROOVES**

Added sipes and grooves improve aquaplaning resistance and provide better handling on wet roads

**DRY GRIP**

Tread design creates a much larger contact area allowing better stability, cornering and control

**ADVANCED TREAD COMPOUND**

Advanced silica tread compound boosts rolling resistance and helps improve fuel efficiency

**LATERAL AND LONGITUDINAL GROOVES**

Deliver smooth handling and better control on dry and wet roads

Additional Sizes Coming Soon!



ALL-SEASON TOURING  
S.U.V. & Crossover H/T Tires



- S.U.V. Sizes - 15, 16, 17, 18, 19 & 20"  
Rim Diameters 55, 60, 65, 70 &  
75 Series Aspect Ratio
- 600 U.T.Q.G.
- 10, 11 & 13/32 Tread Depth
- Uniquely Wide & Flat Tread  
Radius Produces excellent  
steering progression and ride  
comfort.
- High Rubber to void ratio with  
variable shaped tread block  
elements.  
Produces great wear character  
and long mileage.  
Tread block noise is cancelled  
out creating sound comfort.
- Jointless Nylon Band  
Spiral wound for uniformity  
Increases strength in the high  
stress shoulder area.
- 2 Wide Steel Belts  
Strengthen the overall tread area.  
Provides stability, excellent wear  
character & long mileage.
- More sizes on the way



H/T

| Wheel Dia. | TIRE SIZE   | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|-------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 15"        | 235/75R15   | 109T                 | 6.0-6.5-8.0           | 6.0-6.5-8.0           | 6 1/2J            | 8.5            | 235              | 733                 | 1030 2271          | 340 49                  | 600 A B | /          |
| 16"        | 215/70R16   | 100H                 | 5.5-6.5-7.0           | 5.5-6.5-7.0           | 6 1/2J            | 8.5            | 221              | 708                 | 800 1764           | 300 44                  | 600 A B | /          |
|            | LT215/85R16 | 115/112Q             | 5.5-6.0-7.0           | 5.5-6.0-7.0           | 6J                | 9.9            | 216              | 772                 | 1215 2680          | 550 80                  | /       | /          |
|            | 225/70R16   | 103T                 | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 8.5            | 228              | 722                 | 875 1929           | 300 44                  | 600 A B | /          |
|            | LT225/75R16 | 115/112S             | 6.0-7.0               | 6.0-7.5               | 6J                | 9.9            | 223              | 744                 | 1215 2680          | 550 80                  | /       | 10 PR/E    |
|            | 225/75R16   | 104T                 | /                     | 7.5-8.5-10.0          | 6J                | 9.5            | 223              | 744                 | 900 1984           | 300 44                  | 600AB   | /          |
|            | 235/70R16   | 106H                 | 6.0-7.0-8.0           | 6.0-7.0-8.0           | 7J                | 8.5            | 240              | 736                 | 950 2094           | 300 44                  | 600 A B | /          |
|            | LT235/85R16 | 120/116R             | 6.0-6.5-7.5           | 6.0-6.5-7.5           | 6 1/2J            | 9.9            | 235              | 806                 | 1380 3042          | 550 80                  | /       | 10PR/LRE   |
|            | 245/70R16   | 111T                 | 6.5-7.0-8.0           | 6.5-7.0-8.0           | 7J                | 8.5            | 248              | 750                 | 1090 2403          | 340 49                  | 600 A B | /          |
|            | 245/75R16   | 111T                 | 6.5-7.0-8.0           | 6.5-7.0-8.0           | 7J                | 8.5            | 248              | 774                 | 1090 2403          | 300 44                  | 600 A B | /          |
|            | LT245/75R16 | 120/116S             | /                     | 6.5-7.0-8.0           | 7J                | 10.7           | 248              | 774                 | 1380 3042          | 550 80                  | /       | 10 PR/E    |
|            | 255/70R16   | 111T                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8.5            | 260              | 764                 | 1090 2403          | 300 44                  | 600 A B | /          |
|            | 265/70R16   | 112H                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J                | 8.5            | 272              | 778                 | 1120 2469          | 300 44                  | 600 A B | /          |
|            | 265/75R16   | 116T                 | 7.0-7.5-9.0           | 7.0-7.5-9.0           | 7 1/2J            | 8.5            | 267              | 804                 | 1250 2756          | 300 44                  | 600 A B | /          |
|            | LT265/75R16 | 123/120R             | /                     | 7.0-7.5-9.0           | 7 1/2J            | 10.7           | 267              | 804                 | 1550 3415          | 550 80                  | /       | 10PR/LRE   |
| 17"        | 225/65R17   | 102T                 | 6.0-6.5-8.0           | 6.0-6.5-8.0           | 6 1/2J            | 8.5            | 228              | 724                 | 850 1874           | 300 44                  | 600 A B | /          |
|            | 225/65R17   | 102T                 | 6-6.5-7               | 6-6.5-7               | 6.5               | /              | 228              | 724                 | 850 1874           | 300 44                  | 600AB   | 4PR        |
|            | 235/65R17   | 108H                 | 6.5-7.0-8.5           | 6.5-7.0-8.5           | 7J                | 8.5            | 240              | 738                 | 1000 2205          | 340 49                  | 600 A B | /          |
|            | 235/65R17   | 108H                 | 6.5-7-7.5             | 6.5-7-7.5             | 7                 | /              | 240              | 738                 | 1000 2205          | 340 49                  | 600AB   | 4PR        |
|            | LT235/80R17 | 120/117Q E-PLY       |                       | 6.0-6.5-7.5           | 6 1/2J            | 9.9            | 235              | 808                 | 1400 3085          | 550 80                  | /       | 10PR/LRE   |
|            | 245/65R17   | 107H                 | 7.0-8.5               | 7.0-8.5               | 7J                | 8.5            | 248              | 750                 | 975 2149           | 300 44                  | 600 A B | /          |
|            | 245/70R17   | 114H                 | 6.5-7.0-8.0           | 6.5-7.0-8.0           | 7J                | 8.5            | 248              | 776                 | 1180 2601          | 340 49                  | 600 A B | /          |
|            | LT245/70R17 | 119/116_S            | /                     | 6.5-7.0-8.0           | 7J                | 10.7           | 248              | 776                 | 1360 2998          | 550 80                  | /       | 10PR/LRE   |
|            | LT245/75R17 | 121/118S             | /                     | 6.5-7.0-8.0           | 7 J               | 10.7           | 248              | 800                 | 1450 3197          | 550 80                  | /       | 10 PR/E    |
|            | 255/65R17   | 110H                 | 7.0-7.5-9.0           | 7.0-7.5-9.0           | 7 1/2J            | 8.5            | 260              | 764                 | 1060 2337          | 300 44                  | 600 A B | /          |
|            | 255/70R17   | 112H                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8.5            | 260              | 790                 | 1120 2469          | 300 44                  | 600 A B | /          |
|            | 265/65R17   | 116H                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J                | 8.5            | 272              | 776                 | 1250 2756          | 340 49                  | 600 A B | /          |
|            | 265/70R17   | 115H                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J                | 8.5            | 272              | 804                 | 1215 2679          | 300 44                  | 600 A B | /          |
|            | LT265/70R17 | 121/118S             | /                     | 7.0-8.0-9.0           | 8J                | 10.7           | 272              | 804                 | 1450 3197          | 550 80                  | /       | 10 PR/E    |
| 18"        | 235/55ZR18  | 104W                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8.5            | 245              | 715                 | 900 1984           | 340 49                  | 600 A B | /          |
|            | 235/60R18   | 107V                 | 6.5-7.0-8.5           | 6.5-7.0-8.5           | 7J                | 8.5            | 240              | 739                 | 975 2149           | 340 49                  | 600 A B | /          |
|            | 235/60R18   | 107V                 | 6.5-7-7.5             | 6.5-7-7.5             | 7                 | /              | 240              | 739                 | 975 2149           | 340 49                  | 600AB   | 4PR        |

SIZES  
COMING  
SOON

| Wheel Dia. | TIRE SIZE |
|------------|-----------|
| 16"        | 235/60R16 |
| 17"        | 285/65R17 |

| Wheel Dia. | TIRE SIZE |
|------------|-----------|
| 18"        | 285/60R18 |
| 19"        | 265/55R19 |

| Wheel Dia. | TIRE SIZE |
|------------|-----------|
| 20"        | 265/55R20 |
|            | 285/50R20 |

| Wheel Dia. | TIRE SIZE |
|------------|-----------|
| 22"        | 265/50R22 |
|            | 275/45R22 |



ALL-SEASON TOURING  
S.U.V. & Crossover H/T Tires



- S.U.V. Sizes - 15, 16, 17, 18, 19 & 20"  
Rim Diameters 55, 60, 65, 70 &  
75 Series Aspect Ratio
- 600 U.T.Q.G.
- 10, 11 & 13/32 Tread Depth
- Uniquely Wide & Flat Tread  
Radius Produces excellent  
steering progression and ride  
comfort.
- High Rubber to void ratio with  
variable shaped tread block  
elements.  
Produces great wear character  
and long mileage.  
Tread block noise is cancelled  
out creating sound comfort.
- Jointless Nylon Band  
Spiral wound for uniformity  
Increases strength in the high  
stress shoulder area.
- 2 Wide Steel Belts  
Strengthen the overall tread area.  
Provides stability, excellent wear  
character & long mileage.
- More sizes on the way




H/T

| Wheel Dia. | TIRE SIZE   | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|-------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 18"        | 235/65R18   | 110H                 | 6.5-7.0-8.5           | 6.5-7.0-8.5           | 7J                | 8.5            | 240              | 763                 | 1060 2337          | 340 49                  | 600 A B | /          |
|            | 245/60R18   | 105H                 | 7.0-8.5               | 7.0-8.5               | 7J                | 8.5            | 248              | 751                 | 925 2039           | 300 44                  | 600 A B | /          |
|            | 245/60R18   | 105H                 | 6.5-7-7.5             | 6.5-7-7.5             | 7                 | /              | 248              | 751                 | 925 2039           | 300 44                  | 600 A B | 4PR        |
|            | 255/65R18   | 111T                 | 7.0-7.5-9.0           | 7.0-7.5-9.0           | 7 1/2J            | 8.5            | 260              | 789                 | 1090 2403          | 300 44                  | 600 A B | /          |
|            | 255/70R18   | 113H                 | 6.5-7.5-8.5           | 6.5-7.5-8.5           | 7 1/2J            | 8.5            | 260              | 815                 | 1150 2535          | 300 44                  | 600 A B | /          |
|            | 265/60R18   | 114V                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J                | 8.5            | 272              | 775                 | 1180 2601          | 340 49                  | 600 A B | /          |
|            | 265/65R18   | 114H                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J                | 8.5            | 272              | 801                 | 1180 2601          | 300 44                  | 600 A B | /          |
|            | 265/70R18   | 116H                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J                | 8.5            | 272              | 829                 | 1250 2756          | 300 44                  | 600 A B | /          |
|            | 275/65R18   | 116H                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J                | 8.9            | 279              | 815                 | 1250 2756          | 300 44                  | 600 A B | /          |
|            | LT275/65R18 | 123/120_S            | /                     | 8.0-9.5               | 8J                | 11.5           | 279              | 815                 | 1550 3417          | 550 80                  | /       | 10PR/LRE   |
| 19"        | LT275/70R18 | 125/122_S            | /                     | 7.0-8.0-9.0           | 8J                | 11.7           | 279              | 843                 | 1650 3638          | 550 80                  | /       | 10PR/LRE   |
|            | 255/60R19   | 109H                 | 7.0-7.5-9.0           | /                     | 7 1/2J            | 8.5            | 260              | 789                 | 1030 2271          | 300 44                  | 600 A B | /          |
|            | 245/50ZR20  | 102W                 | 7.0-7.5-8.5           | 7.0-7.5-8.5           | 7 1/2J            | 8.5            | 253              | 754                 | 850 1874           | 300 44                  | 600 A B | /          |
|            | 245/60R20   | 107H                 | /                     | 7.0-8.5               | 7J                | 9.5            | 248              | 802                 | 975 2149           | 300 44                  | 600 A B | /          |
|            | 265/60R20   | 112H                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 8.2            | 272              | 826                 | 1120 2469          | 300 44                  | 600 A B | 4PR        |
| 20"        | 275/60R20   | 115V                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J                | 8.9            | 279              | 838                 | 1215 2679          | 300 44                  | 600 A B | /          |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.


PATTERN INTRODUCTIONS




Four wide longitudinal grooves enhance water evacuation, improving cornering and handling performance on wet roads.



3 directional continuous center ribs ensure straight driving stability. Cross-interlocking groove design provides reliable grip and reduces noise. Sharp edges of the lateral grooves cut through water film effectively, and resist hydroplaning of the tire.



Optimization of 5 variable pitch sequence, effectively reduces the noise resonance, improving comfort. Optimized pitch width, effectively improves the load carrying capacity while reducing noise.



Optimized depth of main grooves ensure high mileage. Optimal ratio of tread rib ensures efficient ground contact area while ensuring tire load carrying capacity. Depth of the shoulder grooves design, effectively reduce the tire heat, providing a reliable load durability.

UHP All-Season  
Ultra High Performance

AMERICAN  
ROADSTAR HP A/S



- S.U.V. Sizes - 19, 20, 22, 24 & 26" Rim Diameters 30, 35, 40, 45, 50, & 55 Series Aspect Ratio
- 500 U.T.Q.G.
- 10/32 Tread Depth
- Uniquely Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- Aggressive "Grown-Up" tread design. Produces great traction for all weather and road surfaces. Tightly packed shoulder blocks are quiet and wear evenly.
- Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.



HP A/S

| Wheel Dia. | TIRE SIZE  | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 19"        | 255/50ZR19 | 107Y                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J                | 8              | 265              | 739                 | 975 2149           | 340 49                  | 500 A A | /          |
| 20"        | 275/45R20  | 110V                 | 8.5-9.0-10.5          | 8.5-9.0-10.5          | 9J                | 8.3            | 273              | 756                 | 1060 2337          | 340 49                  | 500 A A | /          |
|            | 275/55R20  | 117V                 | 7.5-8.5-9.5           | 7.5-8.5-9.5           | 8 1/2J            | 8.3            | 284              | 810                 | 1285 2833          | 340 49                  | 500 A A | /          |
| 22"        | 235/30ZR22 | 90W                  | 8.5                   | /                     | 8 1/2J            | 8              | 241              | 701                 | 600 1323           | 340 49                  | 500 A A | /          |
|            | 245/30ZR22 | 95W                  | 8.0-8.5-9.0           | /                     | /                 | /              | /                | /                   | 690 1521           | 340 49                  | 500 A A | /          |
|            | 265/35ZR22 | 102W                 | 9.0-9.5-10.5          | 9.0-9.5-10.5          | 9 1/2J            | 8              | 271              | 745                 | 850 1874           | 340 49                  | 500 A A | /          |
|            | 265/40ZR22 | 106W                 | 9.0-9.5-10.5          | /                     | 9 1/2J            | 8              | 271              | 771                 | 950 2094           | 340 49                  | 500 A A | /          |
|            | 285/45R22  | 114V                 | 9.0-9.5-10.5          | 9.0-9.5-10.5          | 9 1/2 J           | 8.3            | 285              | 815                 | 1180 2601          | 340 49                  | 500 A A | /          |
| 24"        | 305/40R22  | 114V                 | 10.0-11.0-12.0        | 10.0-11.0-12.0        | 11J               | 8.3            | 313              | 803                 | 1180 2601          | 340 49                  | 500 A A | /          |
|            | 295/35ZR24 | 110W                 | 10.0-10.5-11.5        | /                     | 10 1/2J           | 8.3            | 301              | 816                 | 1060 2337          | 340 49                  | 500 A A | /          |
|            | 305/35R24  | 112V                 | 10.0-11.0-12.0        | 10.0-11.0-12.0        | 11J               | 8.3            | 313              | 824                 | 1120 2469          | 340 49                  | 500 A A | /          |
| 26"        | 295/30ZR26 | 107W                 | 10.0-10.5-11.0        | /                     | 10 1/2 J          | 8.3            | 301              | 838                 | 975 2149           | 340 49                  | 500 A A | /          |
|            | 305/30ZR26 | 109V                 | 10.5-11.0-11.5        | /                     | 11J               | 8.3            | 313              | 844                 | 1030 2271          | 340 49                  | 500 A A | /          |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.

PATTERN INTRODUCTIONS



Central longitudinal continuous main rib, provides straight driving stability and high speed controllability ensuring safety. Twin longitudinal main grooves with 3D groove walls are effective in preventing hydroplaning on wet roads, and reduce noise. Continuous blocks ensure efficient ground contact area, providing extreme control and stability.



Zig Zag grooves, cross grooves and sipes improve the all-weather performance of the tire.



With the advanced design concept silica compound and 3D sips distribution ULTRA SPORT A/S provides reliable grip and excellent braking performance in wet and dry conditions.



Optimization of variable random pitch sequence, minimizes noise generation contributing a quiet and comfortable ride.



UHP All-Season  
Ultra High Performance



- 500 U.T.Q.G.
  - 10/32 Tread Depth
  - Uniquely Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
  - Aggressive "Grown-Up" tread design. Produces great traction for all weather and road surfaces. Tightly packed shoulder blocks are quiet and wear evenly.
  - Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
  - 2 Wide Steel Belts Strengthen the overall tread area.
- Provides stability, excellent wear character & long mileage.



RAZZO A/S

| Wheel Dia. | TIRE SIZE | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|-----------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 20" NEW    | 275/55R20 | 117V                 | 7.5-8.5-9.5           | 7.5-8.5-9.5           | 8 1/2J            | 8.1            | 284              | 810                 | 1285 2833          | 340 50                  | 500 A A | /          |
| 22" NEW    | 285/45R22 | 114V                 | 9.0-9.5-10.5          | 9.0-9.5-10.5          | 9 1/2J            | 7.9            | 285              | 815                 | 1180 2601          | 340 50                  | 500 A A | /          |
| NEW        | 305/40R22 | 114V                 | 10.0-11.0-12.0        | 10.0-11.0-12.0        | 11J               | 7.9            | 313              | 803                 | 1180 2601          | 340 50                  | 500 A A | /          |
| 24" NEW    | 305/35R24 | 112V                 | 10.0-11.0-12.0        | 10.0-11.0-12.0        | 11J               | 7.9            | 313              | 824                 | 1120 2469          | 340 50                  | 500 A A | /          |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.

NEW SIZES COMING SOON



RAZZO A/S





HIGHWAY-COMMERCIAL  
All-Season Tires



- Symmetrical/Non-Directional Commercial Hwy A/S
- Speed Ratings – Q, R – 6 PR
- 65-75 Series, 16 in. rim size
- 4 Wide Circumferential Ribs for outstanding strength and load support
- 3 Zigzag Circumferential grooves for water evacuation and all-season traction.
- Made in Thailand
- Designed for drivers of commercial pick-up trucks and vans for rugged all-season commercial use



VAN

| Wheel Dia.             | TIRE SIZE  | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG | PLY RATING |
|------------------------|------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|------|------------|
| 13" <small>NEW</small> | 165R13C    | 94/93R               | /                     | /                     | 4.5               | 7              | 167              | 596                 | 670 1477           | 450 65                  | /    | 8PR        |
| 14" <small>NEW</small> | 185R14C    | 102/100Q             | /                     | /                     | 5.5               | 7.8            | 188              | 650                 | 850 1874           | 450 65                  | /    | 8PR        |
|                        | 195R14C    | 106/104S             | /                     | /                     | 5.5               | 7.8            | 198              | 666                 | 950 2094           | 450 65                  | /    | 8PR        |
| 15" <small>NEW</small> | 185/60R15C | 94/92T               | 5-5.5-6               | 5-5.5-6               | 5.5               | 8.5            | 189              | 603                 | 670 1477           | 375 55                  | /    | 6PR        |
|                        | 195/70R15C | 104/102R             | /                     | /                     | 6                 | 7.8            | 201              | 655                 | 900 1984           | 450 65                  | /    | 8PR        |
|                        | 195R15C    | 106/104S             | /                     | /                     | 5.5               | 7.8            | 198              | 690                 | 950 2094           | 450 65                  | /    | 8PR        |
|                        | 205/70R15C | 106/104S             | /                     | /                     | 6                 | 8.3            | 209              | 669                 | 950 2094           | 450 65                  | /    | 8PR        |
|                        | 215/70R15C | 106/104S             | /                     | /                     | 6.5               | 8.3            | 221              | 683                 | 1030 2271          | 450 65                  | /    | 8PR        |
| 16" <small>NEW</small> | 225/70R15C | 112/110S             | /                     | /                     | 7.5               | 8.7            | 225              | 696                 | 1119 2469          | 450 65                  | /    | 8PR        |
|                        | 195/75R16C | 110/108R 10PLY       | 5.0-5.5-6.0           | /                     | 5 1/2J            | 8.8            | 196              | 698                 | 1060 2335          | 525 77                  | /    | 10PR/LRE   |
|                        | 235/65R16C | 121/119R 10PLY       | 6.5-7.0-7.5           | /                     | 7J                | 8.8            | 240              | 712                 | 1450 3195          | 575 83                  | /    | 10PR/LRE   |
|                        | 285/65R16C | COMING SOON          |                       |                       |                   |                |                  |                     |                    |                         |      |            |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.



ALL-TERRAIN A/T Tires



- SUV Metric Sizes - LT Metric & High Float Sizes 15, 16, 17, 18, 20 & 22" Rim Diameters
- 40, 45, 55, 60, 70 & 75 Series Aspect Ratios
- 12, 13, 15, 16 & 17/32 Tread Depth
- Super Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- Attractive Marked Tread Design Produces great traction for all weather and road surfaces. Wrap around shoulder elements are profound and functional.
- Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.



PATTERN INTRODUCTIONS



- Strong Pattern Block Design Strong central pattern blocks ensure stable handling performance and powerful control force under off-road conditions. Rugged blocks can prevent cutting, scratching and impact damage.
- Solid Square Shoulder Strong shoulder provide adequate dry traction and turning performance.



- Excellent Drainage Performance Four wide longitudinal grooves can evacuate water effectively, enhance handling and steering on wet road surface .
- Special Multi-Angle Sipe Design Irregular sipes design can reduce noise and improve grip on snow-covered roads effectively, to ensure excellent control performance.

A/T

| Wheel Dia. | TIRE SIZE       | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG   | PLY RATING |
|------------|-----------------|----------------------|-----------------------|-----------------------|---------------|----------------|------------------|---------------------|--------------------|-------------------------|--------|------------|
| 15"        | 31x10.50R15LT   | 109S                 | /                     | 7.0-8.5-9.0           | 8 1/2J        | 12.8           | 268              | 775                 | 1030 2270          | 350 50                  | /      | 6PR/LRC    |
| 16"        | NEW 205R16C     | 110/108Q             | /                     | /                     | 6             | 11.4           | 207              | 740                 | 1059 2335          | 440 65                  | /      | 8PR        |
|            | LT245/75R16     | 120/116R             | /                     | 6.5-7.0-8.0           | 7J            | 12.8           | 248              | 774                 | 1380 3042          | 550 80                  | /      | 10PR/LRE   |
|            | 265/70R16       | 112T                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J            | 10.4           | 272              | 778                 | 1120 2469          | 300 44                  | 500 AA | /          |
|            | NEW 275/70R16   | 114S                 | /                     | /                     | 8.5           | 13             | 275              | 792                 | 1179 2601          | 300 44                  | 500AB  | 4PR        |
|            | LT265/75R16     | 123/120R             | /                     | 7.0-7.5-9.0           | 7 1/2J        | 12.8           | 267              | 804                 | 1550 3415          | 550 80                  | /      | 10PR/LRE   |
| 17"        | LT285/75R16     | 126/123R             | /                     | 7.5-8.0-9.5           | 8J            | 13.7           | 286              | 834                 | 1700 3750          | 550 80                  | /      | 10PR/LRE   |
|            | NEW 225/65R17   | 102T                 | 6-6.5-7               | 6-6.5-7               | 6.5           | 10             | 228              | 724                 | 850 1874           | 300 44                  | 500 AA | 4PR        |
|            | NEW 235/65R17   | 104T                 | 6.5-7-7.5             | 6.5-7-7.5             | 7             | 10             | 240              | 738                 | 900 1984           | 300 44                  | 500 AA | 4PR        |
|            | LT245/75R17     | 121/118_S            | /                     | 6.5-7.0-8.0           | 7J            | 12.8           | 248              | 800                 | 1450 3195          | 550 80                  | /      | 10PR/LRE   |
|            | 245/75R17       | 110H                 | 6.5-7.0-8.0           | 6.5-7.0-8.0           | 7J            | 10.4           | 248              | 800                 | 1060 2337          | 300 44                  | 500 AA | /          |
|            | 255/75R17       | 115T                 | 6.5-7.0-8.5           | 6.5-7.0-8.5           | 7J            | 10.4           | 255              | 814                 | 1215 2679          | 300 44                  | 500 AA | /          |
|            | 265/65R17       | 116T                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J            | 10.4           | 272              | 776                 | 1250 2756          | 340 50                  | 500 AA | /          |
|            | 265/70R17       | 113T                 | 7.0-8.0-9.0           | 7.0-8.0-9.0           | 8J            | 10.4           | 272              | 804                 | 1150 2535          | 300 44                  | 500 AA | /          |
|            | LT265/70R17     | 121/118S             | /                     | 7.0-8.0-9.0           | 8J            | 12.8           | 272              | 804                 | 1450 3195          | 550 80                  | /      | 10PR/LRE   |
| 18"        | LT285/70R17     | 121/118Q             | /                     | 7.5-8.5-9.5           | 8 1/2J        | 13.7           | 292              | 832                 | 1450 3195          | 550 80                  | /      | 10PR/LRE   |
|            | NEW 225/55R18   | 102T                 | 6.5-7-7.5             | 6.5-7-7.5             | 7             | 10             | 233              | 705                 | 850 1874           | 340 49                  | 500 AA | 4PR        |
|            | NEW 225/60R18   | 104T                 | 6-6.5-7               | 6-6.5-7               | 6.5           | 10             | 228              | 727                 | 900 1984           | 340 49                  | 500 AA | 4PR        |
|            | NEW 265/60R18   | 114T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8             | 10             | 272              | 775                 | 1180 2601          | 340 49                  | 500 AA | 4PR        |
|            | 265/65R18       | 114H                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J            | 10.4           | 272              | 801                 | 1180 2601          | 300 44                  | 500 AA | /          |
|            | LT265/70R18     | 124/121_S            | /                     | 7.0-8.0-9.0           | 8J            | 12.8           | 272              | 829                 | 1600 3527          | 550 80                  | /      | 10PR/LRE   |
|            | 275/65R18       | 114T                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J            | 10.4           | 279              | 815                 | 1180 2601          | 300 44                  | 500 AA | /          |
|            | LT275/65R18     | 123/120_S            | /                     | 8.0-9.5               | 8J            | 11.5           | 279              | 815                 | 1550 3417          | 550 80                  | /      | 10PR/LRE   |
|            | LT275/70R18     | 125/122S             | /                     | 7.0-8.0-9.0           | 8J            | 12.8           | 279              | 843                 | 1650 3640          | 550 80                  | /      | 10PR/LRE   |
|            | NEW 285/60R18   | 116H                 | /                     | /                     | 8.5           | 7.8            | 292              | 799                 | 1400 3086          | 340 50                  | 500AA  | 4PR        |
| 20"        | NEW LT285/75R18 | 129/126Q             | 7.5-8-8.5             | 7.5-8-8.5             | 8             | 12.3           | 286              | 885                 | 1850 4080          | 550 80                  | /      | 10PR       |
|            | NEW 265/50R20   | 111T                 | 8-8.5-9               | 8-8.5-9               | 8.5           | 10             | 277              | 774                 | 1090 2403          | 340 49                  | 500 AA | 4PR        |
|            | LT265/60R20     | 121/118_S            | /                     | 8.0-9.5               | 8J            | 12.8           | 272              | 826                 | 1450 3197          | 550 80                  | /      | 10PR/LRE   |
|            | 275/55R20       | 117H                 | 7.5-8.5-9.5           | 7.5-8.5-9.5           | 8 1/2J        | 10.4           | 284              | 810                 | 1285 2833          | 340 49                  | 500 AA | /          |
|            | 275/60R20       | 119H                 | 7.5-8.0-9.5           | 7.5-8.0-9.5           | 8J            | 10.4           | 279              | 838                 | 1360 2998          | 340 49                  | 500 AA | /          |
|            | LT275/65R20     | 126/123S             | /                     | 8.0-9.5               | 8J            | 12.8           | 279              | 866                 | 1700 3750          | 550 80                  | /      | 10PR/LRE   |
| 22"        | LT285/55R20     | 122/119S             | /                     | 8.5-9.0-10.0          | 9J            | 12.5           | 297              | 822                 | 1500 3305          | 550 80                  | /      | 10PR/LRE   |
|            | NEW 275/50R22   | 115T                 | 8-8.5-9               | 8-8.5-9               | 8.5           | 10             | 284              | 835                 | 1215 2679          | 340 49                  | 500 AA | 4PR        |
|            | 285/45R22       | 116H                 | 9.0-9.5-10.5          | 9.0-9.5-10.5          | 9 1/2J        | 10             | 285              | 815                 | 1250 2756          | 340 49                  | 500 AA | /          |

SIZES COMING SOON

| Wheel Dia. | TIRE SIZE   |
|------------|-------------|
| 15"        | 255/70R15C  |
| 17"        | LT315/70R17 |

| Wheel Dia. | TIRE SIZE   |
|------------|-------------|
| 18"        | LT285/65R18 |

MUD-TERRAIN  
M/T Tires  
AMERICAN ROAD STAR M/T



- SUV Metric Sizes - High Float  
Sizes 17, 18, 20 & 22"  
Rim Diameters
- 50, Series Aspect Ratios  
& High Float
- 19/32 Tread Depth
- Moderated Rubber to Void Ratio  
Reduces noise, Increases Wear character and Mileage.  
Attractive Marked Tread Design  
Produces great traction for all surface conditions.  
Aggressive & Profound Wrap Around Shoulder Elements are functional.
- 3 Polyester Body Plies for strength and resilience
- 2 Wide Steel Belts  
Strengthen the overall tread area.  
Provides stability, excellent wear character & long mileage.
- Jointless Nylon Band  
Spiral wound for uniformity  
Increases strength in the high stress shoulder area.



AGGRESSIVE  
TREAD DESIGN



LONGER  
TREAD LIFE



STRONGER  
SIDEWALL



QUIETER  
RIDE



SIZES  
COMING  
SOON

| Wheel Dia. | TIRE SIZE     |
|------------|---------------|
| 15"        | LT31x10.50R15 |
|            | 33x12.50R15LT |


| Wheel Dia. | TIRE SIZE     |
|------------|---------------|
| 15"        | 35X12.50R15LT |
| 17"        | LT285/70R17   |

M/T

| Wheel Dia. | TIRE SIZE     | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG | PLY RATING |
|------------|---------------|----------------------|-----------------------|-----------------------|---------------|----------------|------------------|---------------------|--------------------|-------------------------|------|------------|
| 17"        | 33x12.50R17LT | 120Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.5           | 318              | 832                 | 1400 3085          | 450 65                  | /    | 10PR/LRE   |
|            | 35x12.50R17LT | 125Q                 | /                     | 8.0-10.0-10.5         | 10J           | 15.7           | 318              | 883                 | 1650 3640          | 450 65                  | /    | 10PR/LRE   |
| 18"        | 33x12.50R18LT | 122Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.7           | 318              | 832                 | 1500 3305          | 550 80                  | /    | 12PR/LRF   |
|            | 35x12.50R18LT | 128Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.7           | 318              | 883                 | 1800 3970          | 550 80                  | /    | 12PR/LRF   |
| 20"        | 33x12.50R20LT | 119Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.4           | 318              | 832                 | 1360 3000          | 550 80                  | /    | 12PR/LRF   |
|            | 35x12.50R20LT | 125Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.7           | 318              | 883                 | 1650 3640          | 550 80                  | /    | 12PR/LRF   |
| 22"        | 33x12.50R22LT | 114Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.5           | 318              | 832                 | 1180 2600          | 550 80                  | /    | 12PR/LRF   |
|            | 35x12.50R22LT | 121Q                 | /                     | 8.5-10.0-11.0         | 10J           | 15.5           | 318              | 883                 | 1450 3195          | 550 80                  | /    | 12PR/LRF   |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.

PATTERN INTRODUCTIONS



- Excellent Driving Performance  
The optimum ratio of rubber and void on the tread and the special stepped edge treatment removal of dirty under extreme off-road conditions effectively, ensuring the excellent driving performance.
- Water And Snow Drainage Performance  
Wide and deep pattern groove design

enhances the anti-skip performance of tires under rainy and snowy road greatly.



- Excellent Gripping Design  
Solid square shoulder increases the contact area between tread and ground greatly, improves the grip and bearing capacity of wet and dry road, making more stable driving.
- Wearing And Stabbing Resistance  
Aggressive sidewall design prevents damage and enhances grip when in deep mud or rock climbing.



RUGGED-TERRAIN  
R/T Tires



Super aggressive style with refined road manners. Large laterally oriented blocks provide extra biting grip with stepped- edge and bold sidewall elements. Lateral groove and zig-zag valleys create channels for water evacuation and snow traction. With a wide flat contact patch, the stable block design gives constant contact with the road ensuring smooth driving, aggressive grip in handling and outstanding all-weather performance on the road. Off-road, the many biting elements of the sidewalls, blocks and grooves will make short work of rocks, mud, sand or snow.



DUAL  
SIDEWALL  
FINISH  
BLACK/RED



DUAL  
SIDEWALL  
FINISH  
BLACK/WHITE

R/T

| Wheel Dia. | TIRE SIZE         | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|-------------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 16"        | NEW LT265/75R16   | 123/120Q             | 7-7.5-8               | 7-7.5-8               | 7.5               | 13.1           | 267              | 804                 | 1550 3415          | 550 80                  | /       | 10PR       |
|            | NEW 265/65R17     | 116T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 272              | 776                 | 1250 2756          | 340 49                  | 500 A A | 4PR        |
|            | NEW LT265/70R17   | 123/120Q             | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 13.1           | 272              | 804                 | 1550 3415          | 550 80                  | /       | 10PR       |
|            | NEW 265/70R17     | 115T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 272              | 804                 | 1215 2679          | 300 44                  | 500 A A | 4PR        |
|            | NEW LT285/70R17   | 126/123Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 292              | 832                 | 1700 3750          | 550 80                  | /       | 10PR       |
| 17"        | NEW LT295/70R17   | 128/125Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 299              | 846                 | 1800 3970          | 550 80                  | /       | 10PR       |
|            | NEW LT315/70R17   | 128/125Q             | 9-9.5-10              | 9-9.5-10              | 9.5               | 13.1           | 323              | 874                 | 1700 3750          | 550 80                  | /       | 12PR       |
|            | NEW 33x12.50R17LT | 124Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 826                 | 1600 3525          | 550 95                  | /       | 12PR       |
|            | NEW 35x12.50R17LT | 121Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 877                 | 1450 3195          | 650 95                  | /       | 12PR       |
|            | NEW 37x12.50R17LT | 128Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 928                 | 1800 3970          | 450 65                  | /       | 12PR       |
| 18"        | NEW 265/60R18     | 114T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 272              | 775                 | 1180 2601          | 340 49                  | 500 A A | 4PR        |
|            | NEW 265/65R18     | 116T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 272              | 801                 | 1250 2756          | 340 49                  | 500 A A | 4PR        |
|            | NEW LT265/70R18   | 124/121Q             | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 13.1           | 272              | 829                 | 1600 3525          | 550 80                  | /       | 10PR       |
|            | NEW 265/70R18     | 116T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 272              | 829                 | 1250 2756          | 300 44                  | 500 A A | 4PR        |
|            | NEW 275/65R18     | 116T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 279              | 815                 | 1250 2756          | 340 49                  | 560 A A | 4PR        |
|            | NEW LT275/65R18   | 123/120Q             | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 13.1           | 279              | 815                 | 1550 3415          | 550 80                  | /       | 10PR       |
|            | NEW LT275/70R18   | 128/125Q             | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 13.1           | 279              | 843                 | 1650 3640          | 550 80                  | /       | 12PR       |
|            | NEW LT285/65R18   | 125/122Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 292              | 827                 | 1650 3640          | 550 80                  | /       | 10PR       |
|            | NEW LT285/75R18   | 129/126Q             | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 13.1           | 286              | 885                 | 1850 4080          | 550 80                  | /       | 10PR       |
|            | NEW LT295/70R18   | 129/126Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 299              | 871                 | 1850 4080          | 550 80                  | /       | 10PR       |
|            | NEW 33x12.50R18LT | 122Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 826                 | 1500 3305          | 550 80                  | /       | 12PR       |
|            | NEW 35x12.50R18LT | 128Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 877                 | 1800 3970          | 550 80                  | /       | 12PR       |

RUGGED-TERRAIN R/T Tires

AMERICAN ROADSTAR R/T



- AGGRESSIVE TREAD DESIGN
- LONGER TREAD LIFE
- STRONGER SIDEWALL
- QUIETER RIDE



R/T

| Wheel Dia. | TIRE SIZE         | LOAD AND SPEED INDEX | EUROPEAN STANDARD RIM | AMERICAN STANDARD RIM | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG    | PLY RATING |
|------------|-------------------|----------------------|-----------------------|-----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|---------|------------|
| 20"        | NEW 265/50R20     | 111T                 | 8-8.5-9               | 8-8.5-9               | 8.5               | 10             | 277              | 774                 | 1090 2403          | 340 49                  | 500 A A | 4PR        |
|            | 275/55R20         | 117T                 | 7.5-8.5-9.5           | 7.5-8.5-9.5           | 8 1/2J            | 10.5           | 284              | 810                 | 1285 2833          | 340 50                  | 500 A A | /          |
|            | NEW 275/60R20     | 116T                 | 7.5-8-8.5             | 7.5-8-8.5             | 8                 | 10             | 279              | 838                 | 1250 2756          | 340 49                  | 500 A A | 4PR        |
|            | LT275/65R20       | COMING SOON          |                       |                       |                   |                |                  |                     |                    |                         |         |            |
|            | NEW LT285/55R20   | 122/119Q             | 8.5-9-9.5             | 8.5-9-9.5             | 9                 | 13.1           | 297              | 822                 | 1500 3305          | 550 80                  | /       | 10PR       |
|            | NEW LT285/60R20   | 125/122Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 292              | 850                 | 1650 3640          | 550 80                  | /       | 10PR       |
| 20"        | NEW LT285/65R20   | 127/124Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 292              | 878                 | 1750 3860          | 550 80                  | /       | 10PR       |
|            | NEW LT295/60R20   | 126/123Q             | 8-8.5-9               | 8-8.5-9               | 8.5               | 13.1           | 299              | 862                 | 1700 3750          | 550 80                  | /       | 10PR       |
|            | NEW 305/55R20     | 116T                 | 9-9.5-10              | 9-9.5-10              | 9.5               | 10             | 316              | 844                 | 1250 2756          | 300 44                  | 500 A A | 4PR        |
|            | 33x12.50R20LT     | 119Q 12PLY           | /                     | 8.5-10.0-11.0         | 10J               | 12.5           | 318              | 826                 | 1360 3000          | 550 80                  | /       | 12PR/LRF   |
|            | NEW 35x12.50R20LT | 125Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 877                 | 1650 3640          | 550 80                  | /       | 12PR       |
|            | NEW 37x12.50R20LT | 128Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 928                 | 1700 3750          | 450 65                  | /       | 12PR       |
| 22"        | NEW 275/50R22     | 115T                 | 8-8.5-9               | 8-8.5-9               | 8.5               | 10             | 284              | 835                 | 1215 2679          | 340 49                  | 500 A A | 4PR        |
|            | NEW 285/45R22     | 114H                 | 9-9.5-10              | 9-9.5-10              | 9.5               | 10             | 285              | 815                 | 1180 2601          | 340 49                  | 500 A A | 4PR        |
|            | NEW 305/45R22     | 118H                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 10             | 303              | 833                 | 1320 2910          | 340 49                  | 500 A A | 4PR        |
|            | NEW 33x12.50R22LT | 114Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 826                 | 1180 2600          | 550 80                  | /       | 12PR       |
|            | NEW 35x12.50R22LT | 121Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 877                 | 1450 3195          | 550 80                  | /       | 12PR       |
|            | NEW 37x12.50R22LT | 127Q                 | 9.5-10-10.5           | 9.5-10-10.5           | 10                | 13.1           | 318              | 928                 | 1750 3860          | 550 80                  | /       | 12PR       |
| 24"        | 33x12.50R24LT     | 106Q                 | 11-11.5-12            | 11-11.5-12            | 11.5              | 13.1           | 320              | 826                 | 825 1820           | 450 65                  | /       | 12PR       |
|            | 35x12.50R24LT     | 116Q                 | 10-10.5-11            | 10-10.5-11            | 10.5              | 13.1           | 316              | 877                 | 1090 2405          | 450 65                  | /       | 12PR       |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.


PATTERN INTRODUCTIONS




**Lateral Grooves and Zigzag longitudinal design**  
Provide aggressive traction in rain, mud, snow and sand. Rock-crawler looks with impeccable on-highway manners



**Concave and convex sidewall design**  
Concave and convex sidewall extend from the shoulder blocks down to the sidewall for extra off-road traction.



**Stable block design**  
promotes even wear while providing a consistent contact patch and large outside tread elements for great dry handling



**Stepped block edges, stepped block ties**  
Reduce irregular wear, fight stone retention and create additional biting surfaces for traction on wet surfaces, snow and Variable step shape block design for extra bite to get more traction.

RUGGED-TERRAIN  
X R/T Tires

AMERICAN ROADSTAR X R/T NEW



X R/T

| Wheel Dia. | TIRE SIZE     |
|------------|---------------|
| 17"        | 33x12.50R17LT |
|            | 35x12.50R17LT |
| 18"        | 33x12.50R18LT |
|            | 35x12.50R18LT |
| 20"        | 33x12.50R20LT |
|            | 35x12.50R20LT |
| 22"        | 33x12.50R22LT |
|            | 35x12.50R22LT |

Super aggressive style with refined road manners. Large laterally oriented blocks provide extra biting grip with stepped- edge and bold sidewall elements. Lateral groove and zig-zag valleys create channels for water evacuation and snow traction. With a wide flat contact patch, the stable block design gives constant contact with the road ensuring smooth driving, aggressive grip in handling and outstanding all-weather performance on the road. Off-road, the many biting elements of the sidewalls, blocks and grooves will make short work of rocks, mud, sand or snow.



LONGER  
TREAD LIFE



STRONGER  
SIDEWALL



QUIETER  
RIDE

DUAL  
SIDEWALL  
FINISH  
BLACK/RED  
BLACK/WHITE





AMERICAN ROAD STAR ST

NEW  
ST  
SPECIAL TRAILER  
SEMI-STEEL / ST

ST SEMI-STEEL

SEMI-STEEL / ST

| Wheel Dia. | TIRE SIZE       | LOAD AND SPEED INDEX | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG | PLY RATING |
|------------|-----------------|----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|------|------------|
| 13"        | NEW ST175/80R13 | 97/93N               | 5.0JX13           | 7              | 177              | 610                 | 730 1610           | 450 65                  | -    | 8PR        |
|            | NEW ST185/80R13 | 99/95N               | 5.0JX13           | 7              | 184              | 626                 | 670 1480           | 350 50                  | -    | 8PR        |
|            | NEW ST185/80R13 | -                    | -                 | -              | -                | -                   | - -                | - -                     | -    | 6PR        |
| 14"        | NEW ST205/75R14 | 100/96N              | 5.5JX14           | 7              | 203              | 664                 | 800 1765           | 350 50                  | -    | 6PR        |
|            | NEW ST205/75R14 | 105/101N             | 5.5JX14           | 7              | 203              | 664                 | 925 2040           | 450 65                  | -    | 8PR        |
|            | NEW ST215/75R14 | 108/103N             | 6.0JX14           | 7              | 216              | 678                 | 1000 2200          | 450 65                  | -    | 8PR        |
| 15"        | NEW ST205/75R15 | 101/97N              | 5.5JX15           | 7              | 203              | 689                 | 825 1820           | 350 50                  | -    | 6PR        |
|            | NEW ST205/75R15 | 107/102N             | 5.5JX15           | 7              | 203              | 689                 | 975 2150           | 450 65                  | -    | 8PR        |
|            | NEW ST205/75R15 | 111/106N             | 5.5JX15           | 7              | 203              | 689                 | 1090 2400          | 550 80                  | -    | 10PR       |
|            | NEW ST225/75R15 | 113/108N             | 6.0JX15           | 7              | 223              | 719                 | 1150 2540          | 450 65                  | -    | 8PR        |
|            | NEW ST225/75R15 | 117/112N             | 6.0JX15           | 7              | 223              | 719                 | 1285 2830          | 550 80                  | -    | 10PR       |
|            | NEW ST235/85R16 | 125/121N             | 6.5JX16           | 7              | 235              | 806                 | 1650 3640          | 550 80                  | -    | 10PR       |
| 16"        | NEW ST235/85R16 | 128/124N             | 6.5JX16           | 7              | 235              | 806                 | 1800 3960          | 660 95                  | -    | 12PR       |
|            | NEW ST235/80R16 | 124/120N             | 6.5JX16           | 7              | 235              | 782                 | 1600 3520          | 550 80                  | -    | 10PR       |
|            | NEW ST235/80R16 | 127/122N             | 6.5JX16           | 7              | 235              | 782                 | 1750 3860          | 690 100                 | -    | 12PR       |
|            | NEW ST225/90R16 | 129/125N             | 6.0JX16           | 7              | 223              | 810                 | 1750 3860          | 660 95                  | -    | 12PR       |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.



AMERICAN ROAD STAR ST

NEW  
ST  
SPECIAL TRAILER  
ALL-STEEL / ST

ST ALL-STEEL

ALL-STEEL / ST

| Wheel Dia. | TIRE SIZE       | LOAD AND SPEED INDEX | REC RIM WIDTH IN. | TREAD DEPTH MM | SECTION WIDTH MM | OVERALL DIAMETER MM | MAX LOAD KGS   LBS | MAX INFLATION KPA   PSI | UTQG | PLY RATING |
|------------|-----------------|----------------------|-------------------|----------------|------------------|---------------------|--------------------|-------------------------|------|------------|
| 15"        | NEW ST225/75R15 | 123/119N             | 6                 | 8.3            | 223              | 719                 | 1550 3420          | 760 110                 | -    | 14PR       |
| 16"        | NEW ST225/90R16 | 129/125N             | 6                 | 8.3            | 220              | 808                 | 1850 4080          | 760 110                 | -    | 14PR       |
|            | NEW ST225/90R16 | 130/126L             | 6                 | 8.3            | 220              | 808                 | 1900 4190          | 760 110                 | -    | 16PR       |
|            | NEW ST235/80R16 | 129/125N             | 6.5               | 8.3            | 235              | 782                 | 1850 4080          | 760 110                 | -    | 14PR       |
|            | NEW ST235/80R16 | 130/126L             | 6.5               | 8.3            | 235              | 782                 | 1900 4190          | 760 110                 | -    | 16PR       |
|            | NEW ST235/85R16 | 132/127N             | 6.5               | 8.3            | 235              | 806                 | 2000 4400          | 760 110                 | -    | 14PR       |
|            | NEW ST235/85R16 | 133/128L             | 6.5               | 8.3            | 235              | 806                 | 2060 4540          | 760 110                 | -    | 16PR       |





## **ARS 1000 ARS 1100**

SMART WAY

STEER ALL-POSITION



## **ARS 2000 ARS 2200**

SMART WAY

CLOSED-SHOULDER DRIVE



## **ARS 3000**

REGIONAL

OPEN - SHOULDER DRIVE



## **ARS 4000**

TRAILER



## **ARS 5000**

REGIONAL

ON-OFF ROAD / MIXED-SERVICE



## **ARS 6000**

REGIONAL

PICK-UP/DELIVERY / ALL-POSITION



**ARS SERIES**  
COMMERCIAL TBR

**AMERICAN**  
**ROADSTAR**  
TIRES

**COMMERCIAL TRUCK TIRES**



**SMART WAY**  
**STEER / ALL-POSITION**



**ARS1000 ARS1100**

ARS1000- ARS1100 - Premium Fuel-Efficient All-Position Specialized tread compound for low rolling resistance 5 Straight ribs with closed shoulders for constant contact and long wear Sipping, cross grooves and wavy channels at bottom of grooves improve wet traction.

220 Tread width

**ARS 1000 - ARS 1100 SMART WAY / ALL-POSITION**

| SIZE         | PLY  | DEPTH<br>(1/32") | LOAD<br>INDEX | SPEED<br>INDEX | O.D. | S.W. | R.W. | A.P. | MAX LOAD<br>SINGLE | MAX LOAD<br>DUAL |
|--------------|------|------------------|---------------|----------------|------|------|------|------|--------------------|------------------|
| 11R22.5      | 14/G | 18/32            | 144/142       | M              | 41.5 | 11.0 | 8.25 | -    | 6175               | 5840             |
| 11R22.5      | 16/H | 18/32            | 146/143       | M              | 41.5 | 11.0 | 8.25 | 120  | 6610               | 6005             |
| 295/75R22.5  | 14/G | 18/32            | 144/141       | M              | 39.9 | 11.7 | 9.00 | 110  | 6175               | 5675             |
| 295/75R22.5  | 16/H | 18/32            | 146/143       | M              | 39.9 | 11.7 | 9.00 | 120  | 6610               | 6005             |
| 11R24.5      | 14/G | 18/32            | 146/143       | M              | 43.5 | 11.0 | 8.25 | -    | 6610               | 6005             |
| 11R24.5      | 16/H | 18/32            | 149/146       | M              | 43.5 | 11.0 | 8.25 | 120  | 7160               | 6610             |
| *285/75R24.5 | 14/G | 18/32            | 144/141       | M              | 41.3 | 11.1 | 8.25 | -    | 6175               | 5675             |
| *285/75R24.5 | 16/H | 18/32            | 147/144       | M              | 41.3 | 11.1 | 8.25 | 120  | 6780               | 6175             |
| 225/70R19.5  | 14/G | 18/32            | 128/126       | M              | 31.9 | 8.9  | 6.75 | 110  | 3970               | 3750             |
| 225/70R19.5  | 16/H | 18/32            | 129/128       | M              | 31.9 | 9.8  | 6.75 | 120  | 4190               | 3970             |
| 245/70R19.5  | 14/G | 18/32            | 133/131       | M              | 33.0 | 8.9  | 7.50 | 110  | 4540               | 4300             |
| *245/70R19.5 | 16/H | 18/32            | 135/133       | M              | 33.0 | 9.8  | 7.50 | 120  | 4805               | 4540             |
| *255/70R22.5 | 16/H | 18/32            | 140/137       | M              | 36.6 | 10.0 | 7.50 | 120  | 5510               | 5070             |

(\*285/75R24.5) is ARS1100.

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.



ARS 1000 ARS 1100



SMART WAY  
CLOSED-SHOULDER DRIVE



ARS2000 ARS 2200

ARS2000 - ARS2200 - Closed-Shoulder Drive-Position Specialized tread compound for low rolling resistance closed shoulders for constant contact and long wear Large blocks, sipping, cross grooves to improve wet traction Large inside lugs for improved traction in all conditions Stone ejectors in groove to reduce stone drilling  
Extra-deep 28/32 tread for maximum mileage.  
220 Tread width

ARS 2000 - ARS 2200 SMART WAY / CLOSED-SHOULDER DRIVE

| SIZE         | PLY  | DEPTH<br>(1/32") | LOAD<br>INDEX | SPEED<br>INDEX | O.D. | S.W. | R.W. | A.P. | MAX LOAD<br>SINGLE | MAX LOAD<br>DUAL |
|--------------|------|------------------|---------------|----------------|------|------|------|------|--------------------|------------------|
| 11R22.5      | 14/G | 28/32            | 144/142       | M              | 41.9 | 11.0 | 8.25 | -    | 6175               | 5840             |
| 11R22.5      | 16/H | 28/32            | 146/143       | M              | 41.9 | 11.0 | 8.25 | 120  | 6610               | 6005             |
| 295/75R22.5  | 14/G | 28/32            | 144/141       | M              | 40.4 | 11.7 | 9.00 | 110  | 6175               | 5675             |
| 295/75R22.5  | 16/H | 28/32            | 146/143       | M              | 40.4 | 11.7 | 9.00 | 120  | 6610               | 6005             |
| 11R24.5      | 14/G | 28/32            | 146/143       | M              | 43.9 | 11.0 | 8.25 | -    | 6610               | 6005             |
| 11R24.5      | 16/H | 28/32            | 149/146       | M              | 43.9 | 11.0 | 8.25 | 120  | 7160               | 6610             |
| *285/75R24.5 | 14/G | 28/32            | 144/141       | M              | 41.8 | 11.1 | 8.25 | -    | 6175               | 5675             |
| *285/75R24.5 | 16/H | 28/32            | 147/144       | M              | 41.8 | 11.1 | 8.25 | 120  | 6780               | 6175             |

(\*285/75R24.5) is ARS1100.  
Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.

ARS 2000 ARS 2200



ARS 3000 REGIONAL / OPEN - SHOULDER DRIVE

| SIZE        | PLY  | DEPTH<br>(1/32") | LOAD<br>INDEX | SPEED<br>INDEX | O.D. | S.W. | R.W. | A.P. | MAX LOAD<br>SINGLE | MAX LOAD<br>DUAL |
|-------------|------|------------------|---------------|----------------|------|------|------|------|--------------------|------------------|
| 225/70R19.5 | 14/G | 18/32            | 128/126       | N              | 31.9 | 8.9  | 6.75 | 110  | 3970               | 3750             |
| 245/70R19.5 | 16/H | 17/32            | 136/134       | N              | 33.3 | 9.8  | 7.5  | 120  | 4940               | 4675             |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.

REGIONAL / OPEN - SHOULDER DRIVE

ARS3000



To achieve superior traction in all conditions, the ARS3000 features a block pattern with five staggered circumferential rows of blocks. The dense block design along the centerline of the tire ensures excellent load support, quick turning response, and a good on-center feel. Additionally, the continuous contact design guarantees consistent rubber-to-road contact, resulting in predictable grip and even wear.

For efficient water evacuation and improved wet traction, cross grooves and sipes are incorporated, along with efficient circumferential grooves. This ensures that the tire can perform well even in wet conditions, providing reliable and safe handling.

ARS 3000



TRAILER  
**ARS4000**



The ARS4000 trailer tire features a shallow tread, which is intended to reduce the rate of wear and prevent irregular wear. Though it is used on a non-dynamic axle, the casing construction of the ARS4000 is the same as for tires on other wheel positions, which increases the casing's value for retreading.

Serrated rib edges are incorporated into the design to reduce stress while multiple sipes contribute to excellent long-term wear characteristics. To assist with self-cleaning of the tread, serpentine graduated groove walls are incorporated into the design, helping the tire maintain grip in mud & dirt.

Overall, the shallow tread design of the ARS4000 ensures that the tire performs well and lasts longer, providing reliable and cost-effective tire for trailer applications.

**ARS 4000 TRAILER**

| SIZE        | PLY  | DEPTH<br>(1/32") | LOAD<br>INDEX | SPEED<br>INDEX | O.D. | S.W. | R.W. | A.P. | MAX LOAD<br>SINGLE | MAX LOAD<br>DUAL |
|-------------|------|------------------|---------------|----------------|------|------|------|------|--------------------|------------------|
| 11R22.5     | 16/H | 13/32            | 148/145       | M              | 41.5 | 11.0 | 8.25 | 123  | 6945               | 6395             |
| 295/75R22.5 | 14/G | 13/32            | 144/141       | M              | 39.9 | 11.7 | 9.00 | 110  | 6175               | 5675             |
| 11R24.5     | 14/G | 13/32            | 146/143       | M              | 43.5 | 11.0 | 8.25 | 105  | 6610               | 6005             |
| 285/75R24.5 | 14/G | 13/32            | 144/141       | M              | 41.3 | 11.1 | 8.25 | 110  | 6175               | 5675             |

Tire sizes, technical data and product availability are subject to change. Please see [americanroadstar.com](http://americanroadstar.com) for the most up-to-date information.



ARS 5000 ON-OFF / MIXED-SERVICE ALL-POSITION

| SIZE        | PLY  | DEPTH<br>(1/32") | LOAD<br>INDEX | SPEED<br>INDEX | O.D. | S.W. | R.W.  | A.P. | MAX LOAD<br>SINGLE | MAX LOAD<br>DUAL |
|-------------|------|------------------|---------------|----------------|------|------|-------|------|--------------------|------------------|
| 11R22.5     | 16/H | 21/32            | 146/143       | N              | 41.5 | 11.0 | 8.25  | 120  | 6610               | 6005             |
| 275/70R22.5 | 18/J | 18/32            | 148/145       | N              | 37.7 | 10.9 | 8.25  | 131  | 6940               | 6395             |
| 315/80R22.5 | 20/L | 20/32            | 157/154       | N              | 42.4 | 12.3 | 9.00  | 130  | 9090               | 8270             |
| 385/65R22.5 | 20/L | 19/32            | 160           | M              | 42.2 | 15.3 | 11.75 | 130  | 9920               | -                |
| 425/65R22.5 | 20/L | 21/32            | 165           | N              | 44.3 | 16.6 | 12.25 | 120  | 11400              | -                |
| 11R24.5     | 16/H | 21/32            | 149/146       | N              | 43.5 | 11.0 | 8.25  | 120  | 7160               | 6610             |

Tire sizes, technical data and product availability are subject to change. Please see [americanroadstar.com](http://americanroadstar.com) for the most up-to-date information.

ON-OFF / MIXED-SERVICE ALL-POSITION  
**ARS5000**



The all-position mixed-service tread design of the ARS5000 is robust and suitable for many on/off-highway applications. The tire features three large zig-zag circumferential grooves that provide excellent traction in a variety of surface conditions. An indented outside shoulder rib, coupled with zig-zag interior ribs, create grabbing surfaces in mud, rock, and sand.

The tire's resilient tread compound promotes long wear even in harsh conditions, making it ideal for rugged mixed-service applications.

ARS 5000



ARS 6000 REGIONAL / ALL-POSITION

| SIZE        | PLY  | DEPTH<br>(1/32") | LOAD<br>INDEX | SPEED<br>INDEX | O.D. | S.W. | R.W. | A.P. | MAX LOAD<br>SINGLE | MAX LOAD<br>DUAL |
|-------------|------|------------------|---------------|----------------|------|------|------|------|--------------------|------------------|
| 215/75R17.5 | 16/H | 16/32            | 135/133       | L              | 30.2 | 8.3  | 6.00 | 123  | 4805               | 4540             |
| 235/75R17.5 | 18/J | 16/32            | 143/141       | L              | 31.4 | 9.2  | 6.75 | 127  | 6005               | 5675             |
| 245/70R17.5 | 18/J | 16/32            | 143/141       | K              | 31.1 | 9.8  | 7.5  | 130  | 6005               | 5675             |

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.

REGIONAL / ALL-POSITION  
ARS6000



The all-position ARS6000 all-steel radial tire is designed specifically for pick-up/delivery applications, with solid outside ribs that offer strength and resilience to curbing. The undulating circumferential grooves are designed to provide excellent water evacuation, ensuring grip in wet conditions. Additional siping on the interior ribs provides extra biting edges for traction in various surface conditions while serrated center ribs increase traction and reduce irregular wear.

ARS 6000



AMERICAN ROAD STAR  
PASSENGER / LIGHT TRUCK TIRE  
LIMITED WARRANTY

This Limited Warranty is made by WTD (Wholesale Tire Distributor) & applies to the AMERICAN ROAD STAR passenger & light truck tires listed on the summary of Limited Warranty Coverage Chart. The original purchaser is entitled to the benefits of this limited warranty unless a warranty exclusion applies or the purchaser has failed to comply with this Limited Warranty's use, maintenance, or tire rotation requirements. This warranty applies only to tires purchased on or after October 01, 2018

"A. Eligibility for Limited Warranty Coverage

Every tire manufactured and/or marketed by American Road Star, is warranted to be free from defects in material quality or workmanship in its first tread life & warranty period. If our examination shows that such product has failed under the terms of this warranty, we shall replace the product

The warranty is valid exclusively for the first owner using the covered products & is non-transferable. Tampering of any kind on our products will automatically invalidate such warranty (e.g. tampered serial number, ply rating, size of tire, etc).

There is no other warranty or liability applicable to these products, unless specified for a particular size/design, and no representative has any authority to make any representation, promise or agreement except as stated herein.

"B. Warranty - Exclusions and Limitations

1. The warranty does not cover tire damage or irregular wear & tear caused or arising from any of the following reason:

Road hazards including punctures, cuts, snags, bruise, impact breaks etc.;  
Improper use or operation, including without limitation: Improper use such as racing, testing, overloading, improper inflation pressure, fitment not according to the specification of vehicle or wheel manufacturer, negligence, and alterations to the tire;  
Insufficient or improper maintenance, including without limitation: Failure to rotate tires regularly, wheel misalignment, worn suspension components, improper tire mounting or demounting, tire/wheel assembly imbalance, or other vehicle conditions, defects, or characteristics.  
Ride disturbance after the first 25% of usable tread-wear or due to damaged wheels or any vehicle condition.  
Long Storage of new vehicles with tires mounted on, which may cause a flat spot on tire; Contamination or degradation by petroleum products or other chemicals, fire or water. Improper Repair.

2. The warranty does not cover:

Tires worn off beyond tread wear indicator (on either or any one side);  
Tires used for Motor-cross, Rally's etc.;  
Tires damaged due to fire, wreck or vandalism.

"C. Warranty - Disclaimer / Terms & Conditions

American Road Star reserves the right to modify / alter the policy without any advance intimation. The decision of representative of American Road Star after investigation will be final. Liability of American Road Star is limited towards the cost of tire only & does not provide for compensation in case of incidental or consequential damages including loss of use of vehicle and loss of time; The warranty is applicable for the first owner of the product and is not transferrable. Regarding the above warranty policy, there is no other guarantee, warranty, or liability, express or implied, applicable to these products of American Road Star No representative has authority to make any representation, promise or agreement except as stated herein; Tires presented to an authorized American Road Star Dealer for compensation remain the property of the consumer and American Road Star accepts no responsibility for loss or damage to tires which are in the custody or control of an authorized American Road Star Dealer for inspection. The tire will be property of American Road Star once adjusted by American Road Star Customer Service Representative. Consumer holds the responsibility of taking the tire for further inspection, in the event of a dispute, if any; Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. This warranty is not intended as a representation that a tire failure cannot occur. Warranty Period does not represent the expected service life of tires covered under this warranty as the tire life is variable and is dependent on many factors such maintenance of proper inflation pressure , vehicle maintenance practices (such as wheel alignment/balancing, tire rotation & overall vehicle conditions) driving habits, road & operating conditions (terrain etc).

"D Exclusions Not Covered Under This Limited Warranty

- Tires used on RVs (recreational vehicles), Motor Homes, Trailers, or tires used in commercial service.
- Tires that are used in a staggered application where tires on the back of the vehicle are a different size than those on the front.
- Any tire that has any brand information, sizes, or the D.O.T. identification numbers removed intentionally.
- Ride complaints after the first 2/32" of tread wear or replacement of 3 or more tires from the same vehicle will not be accepted.
- Premature/irregular wear due to vehicle mechanical deficiencies.
- Failure to rotate the tires at recommended intervals.
- Road hazard damage including cuts, snags, bruises, punctures, tire repair, impact breaks, etc. (Select tires indicated in this document have coverage under the American Road Star Tire Road Hazard Policy.)
- Any tires on any vehicle that are registered and normally operated outside the U.S.
- Any damage from over/under inflation, tire overloading, fire, theft, and any defective mechanical condition of the vehicle.

- Any damage from incorrect tire mounting/dismounting/ balancing, any incorrect tire application, water or any other material trapped inside the tire during tire mounting.
- Any racing or other misapplication of tire to improper road conditions.
- Environmental ozone or weather cracking after 48 months from tire manufacture date.
- Any accident, fire, chemical corrosion, tire alteration, vandalism, abuse, or running on a flat tire.
- Any tires worn beyond the tire bar wear indicators and less than 2/32".
- Uneven wear in which the tread groove difference is 2/32" or more across the face of the tire.
- Any loss of time or use, inconvenience, any incidental or consequential damage.
- Flat spotting caused by improper storage or brake lock."

"F. Road Hazard Warranty

American Road Star Brand Tires sold in the US by authorized American Road Star Tire dealers, are assigned a Road Hazard Warranty that protects the consumer against non-repairable damage caused by puncture, snag, cut, bruise or impact break. Typical road hazards are nails, glass, potholes and other debris. If a road hazard damage occurs in the first 6 months of ownership, or first 2/32nds whichever comes first, a replacement will be made with a comparable American Road Star Tire 100% free of charge. If a road hazard damage occurs within the 12 months of purchase or when the tire reaches its first 50% of usable tread depth (4/32nd) whichever comes first, American Road Star Tire Dealer will reimburse 50% of their original costs. Under all circumstances, the cost of mounting, balancing and any other service charges including applicable taxes are required to be paid by the consumer.

What is not covered under the Road Hazard Replacement Program?

- A tire that has failed or damaged due to an accident.
- A tire that has failed or damaged due to vandalism.
- A tire that has repairable damage under Rubber Manufacturers Association (RMA) standards.
- A tire that has failed or damaged due to commercial use.
- A tire that has failed or damaged due to racing or off-road use.
- A tire that has failed or damaged due to the use of snow chains or studs.
- A tire that has failed or damaged due to irregular wear caused by mechanical issues.
- Tires transferred from the vehicle that they were originally installed on.
- A tire that is past 2 years from the date of purchase or first 50% of tread wear, whichever comes 1st.- Run-flat tires are not in the scope of this warranty."

LIMITED TIRE WARRANTY REGISTRATION NUMBER  
(To be completed at the time of purchase:)

Date: \_\_\_\_\_ Odometer: \_\_\_\_\_  
**Customer Information:**  
Name: \_\_\_\_\_  
Address: \_\_\_\_\_  
City: \_\_\_\_\_ State: \_\_\_\_\_  
Phone No.: \_\_\_\_\_

**Vehicle Information:**  
Year: \_\_\_\_\_ Make/Model: \_\_\_\_\_  
Tire Brand Purchased: \_\_\_\_\_  
Tire Size/Pattern: \_\_\_\_\_  
Recommended Tire Pressure Front: \_\_\_\_\_ PSI  
Recommended Tire Pressure Rear: \_\_\_\_\_ PSI

**DOT No. Information:**  
Tire #1 \_\_\_\_\_  
Tire #2 \_\_\_\_\_  
Tire #3 \_\_\_\_\_  
Tire #4 \_\_\_\_\_

**Tire Removal Information:**  
Date: \_\_\_\_\_ Odometer: \_\_\_\_\_  
Dealer Name: \_\_\_\_\_  
Dealer Address: \_\_\_\_\_  
**Dealer Signature:** \_\_\_\_\_

**IMPORTANT Tire Owner** – Keep this page as part of your limited warranty claim. (invoice) must be submitted to an authorized American Road Star Tire Dealer  
1. The information on this page must be completed to validate any limited warranty claim.  
2. In the event of a limited warranty claim, this information and proof of purchase (copy of invoice) must be submitted to an authorized American Road Star Tire Dealer.





# AMERICAN ROAD STAR COMMERCIAL TIRE LIMITED WARRANTY

This warranty applies only to tires purchased in the United State on or after October 01, 2018

This Limited Warranty Policy provides for tire replacement under certain specified conditions. This policy applies to all AMERICAN ROADSTAR Radial Truck tires used in normal highway service displaying warrant able conditions. There is no warranty for tires that wear out, fail or become unserviceable because of neglect or mistreatment. It is essential that you adhere to all standard safety and maintenance practices and that you carefully read the terms and conditions defined in this Warranty. Wholesale Tire Distributors hereby warrants that every new AMERICAN ROAD STAR Radial Truck tire is free from defects in workmanship and material for the life of the original tread of the new tire less 2/32". The life of the original usable tread ends when the tire has worn down with only 2/32" remaining. Once the tread is worn down to the top of the built-in "wear indicators" in the tread grooves molded at 2/32", the tire is considered fully worn out regardless of its age or mileage. This warranty applies to AMERICAN ROAD STAR Radial Truck tires purchased through an authorized dealer of Wholesale Tire Distributors (WTD)

RECOMMENDED SAFETY PRACTICES

Serious injury or property damage may result from:

- TIRE FAILURE DUE TO UNDERINFLATION, OVERINFLATION and/or OVERLOADING
- Not following the owner's manual or tire placard in vehicle
- TIRE FAILURE DUE TO EXCESSIVE HIGH SPEED. Follow the owner's manual or tire placard in vehicle.
- EXPLOSION OF TIRE /RIM ASSEMBLY DUE TO IMPROPER MOUNTING. Only specially trained people should mount tires.
- FAILURE TO MOUNT RADIAL TIRES ON APPROVED RIMS.
- FAILURE TO DEFLATE SINGLE OR DUAL ASSEMBLIES COMPLETELY BEFORE DISMOUNTING.
- TIRE SPINNING. On slippery surfaces such as rain, snow, mud, ice etc. do not spin tires as personal injury and severe damage may result from excessive wheel spinning, including tire disintegration or axle damage.

WARRANTY ELIGIBILITY

This policy applies to the original equipment and aftermarket consumer/owner, or user of any new AMERICAN ROAD STAR radial truck tire sold through an authorized dealer of Wholesale Tire Distributors. Eligible tires must bear the AMERICAN ROAD STAR brand name, a complete D.O.T. serial identification number, NOT be branded as Non-Adjustable (NA) and operated in normal highway service. Eligible tires must be on the vehicle on which they were originally installed, in conformance with the vehicle manufacturer's recommendations. These tires are covered by this warranty for the life of the original usable tread depth (the original tread depth down to the level of treadwear indicators molded at 2/32 inch) within 72 months from the date of purchase (proof of purchase required). If proof of purchase is not available, the coverage will be 72 months from the date of manufacture.

NO CHARGE ADJUSTMENT

If a defect in workmanship and materials is found in any AMERICAN ROAD STAR Radial Truck tire within the first 50% of the original usable tread (original tread depth, less 2/32", divided by 2), Wholesale Tire Distributors will replace such tire with a comparable new tire. Mounting and balancing services up to \$16.00/tire are covered in the form of a credit on the replacement tire invoice. Other applicable taxes and fees for the comparable new AMERICAN ROAD STAR tire are payable by the owner.

50% FREE REPLACEMENT WARRANTY

If a defect in workmanship and materials is found in any AMERICAN ROAD STAR Radial Truck tire after the first 50% of the original usable tread, a credit will be given toward the purchase of a comparable new AMERICAN ROAD STAR tire; pro-rated based on the usable tread depth remaining on the returned tire versus the original tread of the new tire. Applicable taxes and amount equal to the full current Federal Excise Tax (FET) on the new tire and costs of mounting and balancing services will be borne by the owner. Adjustments on out-of-balance or out-of-round tires are allowed only during the first 2/32" or 10% of the original tread.

EXCLUSIONS

A. All AMERICAN ROAD STAR warranties are limited to the original purchaser and the original vehicle on which they are mounted. Warranties are not assignable to subsequent purchasers or vehicles.

B. This limited warranty is valid only in the United States. Any tire used or equipped on a vehicle registered or regularly operated outside the United States is not covered by this warranty.

C. The following is not covered by the Limited Warranty:

- a. Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
- b. Failure, damage or irregular wear due to:
  - Road hazards (i.e., puncture, cut, snag, impact breaks, etc.), wreck or collision.
  - Fire, accident or vandalism.
  - Mechanical condition of vehicle, including misalignment, wheel imbalance, faulty shocks or brakes.
  - Misapplication of tire, use of improper inner tube.
  - Alteration of the tire or addition of alien material or transfer from one vehicle to another.
  - Faulty retreading or repairing procedures or materials used in the retreading process.
- c. Cost of mounting and balancing services except as noted.
- d. Loss of time or use, inconvenience, or any incidental or consequential damages.
- e. Tires operated at speeds that exceed posted limits, and tires used in racing or competition.
- f. Tires used in non-standard applications.
- g. Tires designed for highway use operated in off-road conditions.
- h. Tires that are improperly repaired including, but not limited to; sidewall modification by addition or removal of material, tubeless tires into which anything other than air has been introduced including foam, dry or liquid balancers and sealants.
- i. Tire/tube failure and air loss that has resulted from tube manufacturing deficiencies, tube deterioration, tire under/over inflation, improper tube and flap assembly, mounting tool damage, use of wrong size tube or a used tube, a bias tube in a radial application, applying an incompatible mounting lubricant, foreign objects contacting tube assembly.
- j. Wholesale Tire Distributors does not warrant tubes, tube fitment, tube usage or the consequences thereof unless supplied by Wholesale Tire Distributor with the tire as a set.
- k. Tires subjected to vehicle suspension deficiencies, wheels misalignment, improperly maintained balance of inflation
- l. Tires submitted for ride disturbance complaints after the first two thirty-seconds of an inch (2/32") new tread wear.
- m. Tires with the Department of Transportation (DOT) number removed.
- n. Tires worn past the last two thirty-seconds of an inch (2/32") of original tread depth.
- o. Ozone cracking or weather checking on tires submitted more than four years (4) after the date of manufacture.
- a. Tires rendered not retreadable or unserviceable due to faulty or improper retreading. Improper retreading includes buffing to the cord surface, insufficient vulcanization, improper repair and failure of the bonding agent.
- b. Wholesale Tire Distributor Tire does not warrant inspection for retread ability, the retread process, design, workmanship or materials.

CASING POLICY

a. Casings of AMERICAN ROAD STAR radial truck tires are warranted against defects in workmanship and material throughout the first and second retread (see c. below for age restrictions). Defects in workmanship and material found in the process of buffing for retread are warrant able. The number of retreads must be clearly identified on the casing sidewall.

b. If an examination shows that a casing of an AMERICAN ROAD STAR radial truck tire failed due to a defect in workmanship or material, Wholesale Tire Distributors will give a credit towards the purchase price of a comparable new AMERICAN ROAD STAR tire based on the values listed below:

| SIZE        | CASING VALUE (US\$) | SIZE        | CASING VALUE (US\$) |
|-------------|---------------------|-------------|---------------------|
| 215/75R17.5 | \$20                | 295/75R22.5 | \$65                |
| 235/75R17.5 | \$20                | 11R24.5     | \$65                |
| 255/70R22.5 | \$55                | 285/75R24.5 | \$65                |
| 275/70R22.5 | \$55                | 12R22.5     | \$65                |
| 225/70R19.5 | \$25                | 315/80R22.5 | \$65                |
| 245/70R19.5 | \$25                | 385/65R22.5 | \$75                |
| 10R22.5     | \$45                | 425/65R22.5 | \$80                |
| 11R22.5     | \$65                | 445/50R22.5 | \$80                |

c. Above casing warranty valid only for first six (6) years after date of manufacture of original tire for all casings. Casing value is reduced by 50% of the above values for the second retread.

OWNERS' OBLIGATIONS

In order to be eligible for AMERICAN ROAD STAR Limited Warranty service, the owner must:

- Present the defective tire to an authorized AMERICAN ROAD STAR dealer.
- Present proof of purchase to the satisfaction of the dealer.
- Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges (except as noted) or cost of other services ordered.
- Ensure proper tire maintenance, inflation pressures & loading practices in accordance with vehicle and applicable tire guides, as well as lawful operation of vehicles and adherence to government regulations. Wholesale Tire Distributors offers a guide to maintenance and care of AMERICAN ROAD STAR tires in the form of a section entitled, "Safety Practices" (above). It is strongly recommended that these guidelines be read.

LEGAL RIGHTS

To the extent permitted by law, Wholesale Tire Distributors and its servicing agents shall not be held responsible for any of the following:

- Commercial Loss.
- Damage to or loss of property other than the tire itself.
- Incidental, indirect, special or consequential damages arising from any cause whatsoever, including negligence.

Some states do not allow the exclusion or limitation. of incidental or consequential damages, so the above limitation or exclusions may not apply to you. No representative or dealer has authority to make any representation, promise, or agreement on behalf of Wholesale Tire Distributors except as stated herein. Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances is this representation that a tire failure cannot occur. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state. This limited warranty is applicable only in the United States. No implied or express warranties are extended beyond the time when the tire has delivered its original tread life, except for the express warranties set forth in this "Limited Warranty". All warranties, promises and agreements, express or implied, merchantability or otherwise, are excluded to the extent permitted by law.

DISCLAIMER

This warranty, or any warranty stored or referenced to herein, is exclusive and in lieu of any other warranty regarding the quality of AMERICAN ROAD STAR tires whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.



AMERICAN  
ROAD STAR  
TIRES



SUMMARY OF LIMITED TIRE WARRANTY COVERAGE BY  
AMERICAN ROAD STAR TREAD PATTERN

| Pattern / Product Name                      | Tread Wear/Mileage<br>Warranty | Road Hazard<br>Replacement<br>Warranty | First Year /<br>First 2/32nds | Second Year &<br>Within the First 50% of<br>Tread Depth |
|---------------------------------------------|--------------------------------|----------------------------------------|-------------------------------|---------------------------------------------------------|
| ProA/S - AllRim Diameters                   | 50,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| Sport A/S - 15,16 &17" Rim Diameters        | 50,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| Sport A/S - 18,19,20,22 & 24" Rim Diameters | 40,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| HP A/S - All Rim Diameters                  | 40,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| Pro H/T - SUV only                          | 50,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| Eco Pro H/T2                                | 55,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| All Terrain A/T                             | 50,000 Miles                   | Yes                                    | Free                          | Prorated                                                |
| Mud Terrain M/T                             | N/A                            | N/A                                    | N/A                           | N/A                                                     |
| Rugged Terrain R/T                          | N/A                            | N/A                                    | N/A                           | N/A                                                     |
| TBR ARS1000 / ARS1100                       | N/A                            | N/A                                    | N/A                           | N/A                                                     |
| TBR ARS2000 / ARS2200                       | N/A                            | N/A                                    | N/A                           | N/A                                                     |

\*\* LT Metric Sizes is not included in this Limited Mileage and Road Hazard Warranty.  
\*\* Eligible tires for this warranty must meet the vehicle specifications of the original size applied at Original Equipment

NOTE: In the event of a warranty claim, this page must be attached to the American Road Star standard claim form.



AMERICAN ROADSTAR TIRES BF.1



**AMERICAN**  
**ROAD**  **STAR**  
**TIRES**

 [WWW.AMERICANROADSTAR.COM](http://WWW.AMERICANROADSTAR.COM)  
 [@americanroadstartires](https://www.instagram.com/americanroadstartires)